

Technical data

H 11i P



Soil Compactors Series H
Soil compactor with padfoot drum

H266

HIGHLIGHTS

- > Operating concept Easy Drive
- > Electronic machine management Hammtronic
- > 3-point articulation for outstanding traction and off-road mobility
- > High compaction performance thanks to high line load and big amplitudes
- > Excellent view of the machine and the construction site

TECHNICAL DATA H 11i P (H266)

Weights

Operating weight with cab	kg	11975
Operating weight with ROPS	kg	11725
Operating weight, max.	kg	13110
Axle load, front/rear	kg	6550/5425
French classific., data/class		40,9/VPM3

Machine dimensions

Total length	mm	5960
Total height with cab	mm	3088
Total height with ROPS	mm	3137
Height loading, min.	mm	2308
Wheel base	mm	3149
Total width with cab	mm	2284
Max. working width	mm	2140
Ground clearance, centre	mm	427
Kerb clearance, left/right	mm	510/510
Turning radius, inside	mm	3870
Angle of driving slope, front/rear	°	55/30

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1684
Drum thickness, front	mm	15
Drum type, front		Padfoot
Height of the padfeet	mm	100
Padfeet, number		140

Wheel dimensions

Size of tyres, rear		TR 23.1-26 12 PR
Width over tyres, rear	mm	2160
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Version		TCD 3.6 L4
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		85,0/115,6/2300
Power rating SAE J1349, kW/HP/rpm		85,0/113,9/2300
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Drive

Speed, infinitely variable	km/h	0-12,0
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	57/62

Vibration

Vibration frequency, front, I/II	Hz	30/36
Amplitude, front, I/II	mm	1,90/0,80
Centrifugal force, front, I/II	kN	246/136

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L	280
AdBlue/DEF tank, content	L	32

Sound level

Sound power level L(WA), guaranteed	db(A)	104
Acoustic power L(WA), measured	db(A)	103

EQUIPMENT

12 V sockets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Vibration-isolated operator's platform | Automatic vibration system

OPTIONAL EQUIPMENT

Working lights | Dashboard cover | ROPS cabin with heating and air conditioning, FOPS-approved (level I) | Coming home lighting | Tachograph | Fire extinguisher | HCQ Navigator | Automatic engine-off function | Radio | Rotating beacon | Padfoot shells | HCQ compaction meter