



## **HIGHLIGHTS**

- > 3-point articulation for outstanding traction and off-road mobility
- > High compaction performance thanks to high line load and big amplitudes
- > Operating concept Easy Drive
- > Electronic machine management Hammtronic
- > Excellent view of the machine and the construction site

H 12i | **TECHNICAL DATA** HAMM

## **TECHNICAL DATA H 12i (H266)**

Weights		
Operating weight with cab	kg	11715
Operating weight with ROPS	kg	11465
Max. operating weight	kg	14120
Axle load, front/rear	kg	6325/5390
Static linear load, front	kg/cm	30,0
French classification, value/class		41,8/VM3
Machine dimensions		
Total length	mm	5960
Total height with cab	mm	3037
Total height with ROPS	mm	3077
Height loading, min.	mm	2308
Centre distance	mm	3149
Total width with cab	mm	2284
Maximum working width	mm	2140
Ground clearance, centre	mm	427
Kerb clearance, left/right	mm	510/510
Turning radius, inside	mm	3870
Slope angle, front/rear	0	55/30
Drum dimensions		
Drum width, front	mm	2140
Drum diameter, front	mm	1504
Drum thickness, front	mm	25
Drum type, front		Smooth
Tyre dimensions		
Tyre size, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2160
Number of tyres, rear		2
Diesel engine		
Manufacturer		DEUTZ
Model		TCD 3.6 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		85,0/115,6/2300
Power SAE J1349, kW/HP/rpm		85,0/113,9/2300
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR
Travel drive		
Speed, infinitely variable	km/h	0-12,0
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	54/59
Vibration		
Vibration frequency, front, I/II	Hz	30/36
Amplitude, front, I/II	mm	2,04/0,84
Centrifugal force, front, I/II	kN	246/136
Steering		
Swing angle +/-	٥	10
Steering, type		Articulated steering
Tank capacity/filling capacity		
Fuel tank, capacity	L	280
carrier	_	

Tank capacity/filling capacity			
AdBlue/SCR reducing agent tank, capacity	L	32	
Sound level			
Sound power level L(WA), guaranteed	db(A)	104	
Sound power level L(WA), representative measurement	db(A)	103	

## **EQUIPMENT**

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

## **OPTIONAL EQUIPMENT**

Working spotlights | Dashboard cover | ROPS cab with heating and air-conditioning system (FOPS, level I) | Coming Home function | Tachograph | Fire extinguisher | HCQ Navigator | Automatic engine stop | Radio | Rotating beacon | Padfoot shells | HCQ compaction meter

