

Technical data

# HD 10C VT



**Tandem rollers Series HD CompactLine**  
Tandem roller with vibrating roller drum and set of wheels

**H263**

## HIGHLIGHTS

- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Clear Side — one-sided drum suspension
- > Compact dimensions
- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation

## TECHNICAL DATA HD 10C VT (H263)

## Weights

Operating weight with ROPS	kg	1640
Max. operating weight	kg	1740
Static linear load, front	kg/cm	8,1
French classification, value/class		8,1/PV1

## Machine dimensions

Total length	mm	2309
Total height with ROPS	mm	2210
Height loading, min.	mm	1580
Centre distance	mm	1560
Total width	mm	1070
Maximum working width	mm	1000
Turning radius, inside	mm	2130

## Drum dimensions

Drum width, front	mm	1000
Drum diameter, front	mm	620
Drum thickness, front	mm	12
Drum type, front		Smooth/non-split

## Tyre dimensions

Tyre size, rear		205/60-R15
Width over tyres, rear	mm	1000
Number of tyres, rear		4

## Diesel engine

Manufacturer		KUBOTA
Model		D1105
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		16,1/21,9/2600
Power SAE J1349, kW/HP/rpm		16,1/21,6/2600
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust emissions category, EU		EU Stage V
Exhaust emissions category, USA		EPA Tier 4
Exhaust gas after-treatment		-

## Travel drive

Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, I/II	Hz	61/48
Amplitude, front, I/II	mm	0,38/0,38
Centrifugal force, front, I/II	kN	17/11

## Steering

Swing angle +/-	°	8
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	33
Water tank, capacity	L	70

## Tank capacity/filling capacity

Additive tank, capacity	L	9
-------------------------	---	---

## Sound level

Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	101

## EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling system | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

## OPTIONAL EQUIPMENT

Plastic scraper, folding | Additional drive lever, left | Protective roof | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Battery isolation switch | Engine hood with sound insulation | Water drain valve | Tool kit