

Technical data

HD 10C VT



Tandem rollers Series HD CompactLine

Tandem roller with vibrating roller drum and set of wheels

H263

HIGHLIGHTS

- > Excellent view of drum edge, machine and construction site environment
- > Clear Side — one-sided drum mounting
- > Compact dimensions
- > Simple transport, simple loading
- > Simple, intuitive and language-neutral control

TECHNICAL DATA HD 10C VT (H263)

Weights

Operating weight with ROPS	kg lbs	1640 3,616
Max. operating weight	kg lbs	1740 3,837
Static linear load, front	kg/cm lbs/in	8,1 45.4
French classification, value/class		8,1/PV1

Machine dimensions

Total length	mm in	2309 90.9
Total height with ROPS	mm in	2210 87.0
Height loading, min.	mm in	1580 62.2
Center distance	mm in	1560 61.4
Total width	mm in	1070 42.1
Maximum working width	mm in	1000 39.4
Turning radius, inside	mm in	2130 83.9

Drum dimensions

Drum width, front	mm in	1000 39.4
Drum diameter, front	mm in	620 24.4
Drum thickness, front	mm in	12 0.5
Drum type, front		Smooth/non-split

Tire dimensions

Tire size, rear		205/60-R15
Width over tires, rear	mm in	1000 39.4
Number of tires, rear		4

Diesel engine

Manufacturer		Kubota
Model		D1105
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		16,1/21,9/2600
Power SAE J1349, kW/HP/rpm		16,1/21,6/2600
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust emissions category, EU		EU Stage V
Exhaust emissions category, USA		EPA Tier 4
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h mph	0 - 11,0 0.0 - 6.8
----------------------------	-------------	-----------------------

Travel drive

Gradeability, with/without vibration	%	30/40
--------------------------------------	---	-------

Vibration

Vibration frequency, front, I/II	Hz vpm	61/48 3,660/2,880
Amplitude, front, I/II	mm in	0,38/0,38 .015/.015
Centrifugal force, front, I/II	kN lbs	17/11 3,825/2,475

Steering

Swing angle +/-	°	8
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	33 8.7
Water tank, capacity	L Gal	70 18.5
Additive tank, capacity	L Gal	9 2.4

Sound level

Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	101

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling system | Driver's platform with entry from both sides | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, foldable | Additional drive lever, left | Protective roof | Automatic engine-off function | Back-up alarm | Working light | Rotating beacon | Battery isolating switch | Bonnet with sound insulation | Water drain valve | Additional mirror | Tool kit