

Technical data



Tandem rollers Series HD CompactLine Tandem roller with two vibrating roller drums H263

HIGHLIGHTS

- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation
- > Clear Side one-sided drum suspension

TECHNICAL DATA HD 10C VV (H263)

Weights			
Operating weight with ROPS	kg	1680	
Maximum operating weight	kg	1780	
Static linear load, front/rear	kg/cm	8,2/8,7	
French classification, value/class		8,7/PV2	
Machine dimensions			
Total length	mm	2295	
Total height with ROPS	mm	2210	
Height loading, min.	mm	1580	
Centre distance	mm	1560	
Total width	mm	1134	
Maximum working width	mm	1070	
Turning radius, inside	mm	2130	
Drum dimensions			
Drum width, front/rear	mm	1000/1000	
Drum diameter, front/rear	mm	620/620	
Drum thickness, front/rear	mm	12/12	
Drum type, front		Smooth/non-split	
Drum type, rear		Smooth/non-split	
Diesel engine			
Manufacturer		Kubota	
Model		D1105-E4B	
Cylinders, quantity		3	
Power ISO 14396, kW/PS/rpm		16,1/21,9/2600	
Power SAE J1349, kW/HP/rpm		16,1/21,6/2600	
Exhaust emission standard		EU Stage V / EPA Tier 4	
Exhaust emissions category, EU		EU Stage V	
Exhaust emissions category, USA		EPA Tier 4	
Exhaust gas after-treatment		-	
Travel drive			
Speed, infinitely variable	km/h	0 - 11,0	
Gradeability, with/without vibration	%	30/40	
Vibration			
Vibration frequency, front, I/II	Hz	61/48	
Vibration frequency, rear, I/II	Hz	61/48	
Amplitude, front, I/II	mm	0,38/0,38	
Amplitude, rear, I/II	mm	0,38/0,38	
Centrifugal force, front, I/II	kN	17/11	
Centrifugal force, rear, I/II	kN	17/11	
Steering			
Pendulum angle +/-	o	8	
Steering, type		Articulated steering	
Water-sprinkling system			
Water sprinkling, type		Pressure	
Tank capacity/filling capacit	ty	· 	
Fuel tank, capacity	L	33	
Water tank, capacity	L	70	

Sound level		
Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	100

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weatherresistant | Clear Side | Pressure water sprinkling system | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, folding | Additional drive lever, left | Protective roof | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Battery isolation switch | Engine hood with sound insulation | Water drain valve | Tool kit

HAMM

