

# Technical data

Tandem rollers Series HD CompactLine Tandem roller with two vibrating roller drums

H263

W HAMM

# **HIGHLIGHTS**

- > Simple, intuitive and language-neutral operation
- > Clear Side one-sided drum suspension
- > Easy transport, simple loading
- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings

#### **TECHNICAL DATA HD 8 VV (H263)**

Weights		
Operating weight with ROPS	kg	1590
Max. operating weight	kg	1690
Static linear load, front/rear	kg/cm	9,6/10,3
French classification, value/class		10,3/PV3
Machine dimensions		
Total length	mm	2295
Total height with ROPS	mm	2210
Height loading, min.	mm	1580
Centre distance	mm	1560
Total width	mm	938
Maximum working width	mm	872
Ground clearance, centre	mm	230
Turning radius, inside	mm	2230
Drum dimensions		
Drum width, front/rear	mm	800/800
Drum diameter, front/rear	mm	620/620
Drum thickness, front/rear	mm	12/12
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Diesel engine		
Manufacturer		KUBOTA
Model		D1105
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		16,1/21,9/2600
Power SAE J1349, kW/HP/rpm		16,1/21,6/2600
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust emissions category, EU		EU Stage V
Exhaust emissions category, USA		EPA Tier 4
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, I/II	Hz	61/48
Vibration frequency, rear, I/II	Hz	61/48
Amplitude, front, I/II	mm	0,43/0,43
Amplitude, rear, I/II	mm	0,43/0,43
Centrifugal force, front, I/II	kN	17/11
Centrifugal force, rear, I/II	kN	17/11
Steering	NIN	
	0	8
Swing angle +/- Steering, type		8 Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capacit		
Fuel tank, capacity	L	33
Water tank, capacity	L	70

 
 Sound level

 Sound power level L(WA), guaranteed
 db(A)
 105

 Sound power level L(WA), representative measurement
 db(A)
 101

### EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weatherresistant | Clear Side | Pressure water sprinkling system | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

## **OPTIONAL EQUIPMENT**

Plastic scraper, folding | Additional drive lever, left | Protective roof | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Battery isolation switch | Engine hood with sound insulation | Water drain valve | Tool kit

HAMM AG • Hammstr. 1 • D-95643 Tirschenreuth • Tel +49 9631 80-0 • Fax +49 9631 80-111 • www.hamm.eu Further data on request/subject to change Illustrations may contain optional features.© Hamm AG 2023 - 2719010 en-GB V11

