



HIGHLIGHTS

- > Reinforced machine components for high durability
- > High compaction performance thanks to high line load and big amplitudes
- > Operating concept Easy Drive
- > 3-point articulation for outstanding traction and off-road mobility
- > Highly wear resistant drum for hard rock application

TECHNICAL DATA H 25i C R (H268)

Weights		
Operating weight with cab	kg	24880
Basic weight no cab, without ROPS	kg	24130
Operating weight, max.	kg	25270
Axle load, front/rear	kg	16390/8490
French classific., data/class		101,5/VM5
Load per tyre, rear	kg	4245
Machine dimensions		
Total length	mm	6751
Total height with cab	mm	2970
Height loading, min.	mm	2320
Wheel base	mm	3261
Total width with cab	mm	2540
Ground clearance, centre	mm	400
Turning radius, inside	mm	4760
Angle of driving slope, front/rear	0	40/28
Drum dimensions		
Drum width, front	mm	2220
Drum diameter, front	mm	1600
Drum thickness, front	mm	45
Drum type, front		
Wheel dimensions		
Size of tyres, rear		EM 23.5-R25 XTLA
Width over tyres, rear	mm	2160
Number of tyres, rear		2
Diesel engine		
Manufacturer		DEUTZ
Version		TCD 6.1 L6
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		160,0/217,6/2300
Power rating SAE J1349, kW/HP/rpm		160,0/214,4/2300
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR
Drive		DOC-DIT-SCR
Speed, infinitely variable		DOC-DIT-SCK
Regulation, infinitely variable	km/h	0 - 6,9
Climbing ability, vibration on/off	km/h	
Vibration	km/h %	0 - 6,9
		0 - 6,9 Hammtronic/manual
Vibration frequency, front, I/II	%	0 - 6,9 Hammtronic/manual
Vibration frequency, front, I/II Amplitude, front, I/II	%	0 - 6,9 Hammtronic/manual 61/66
	% Hz	0 - 6,9 Hammtronic/manual 61/66 27/30
Amplitude, front, I/II	% Hz mm	0 - 6,9 Hammtronic/manual 61/66 27/30 2,02/1,20
Amplitude, front, I/II Centrifugal force, front, I/II	% Hz mm	0 - 6,9 Hammtronic/manual 61/66 27/30 2,02/1,20
Amplitude, front, I/II Centrifugal force, front, I/II Steering	% Hz mm kN	0 - 6,9 Hammtronic/manual 61/66 27/30 2,02/1,20 315/231
Amplitude, front, I/II Centrifugal force, front, I/II Steering Oscillation angle +/-	% Hz mm kN	0 - 6,9 Hammtronic/manual 61/66 27/30 2,02/1,20 315/231
Amplitude, front, I/II Centrifugal force, front, I/II Steering Oscillation angle +/- Steering, type	% Hz mm kN	0 - 6,9 Hammtronic/manual 61/66 27/30 2,02/1,20 315/231

Sound level		
Sound power level L(WA), guaranteed	db(A)	106
Acoustic power L(WA), measured	db(A)	104

EQUIPMENT

12 V sockets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Automatic vibration system | Lighting package as per road traffic regulations | Camera system

OPTIONAL EQUIPMENT

ROPS cabin with heating and air conditioning, FOPS-approved (level I) |
Safety belt monitoring device | Auxiliary heater | Radio | Tachograph |
Bluetooth interface for Smart Doc | HCQ Navigator | Frequency
regulation | HAMM Compaction Meter (HCM) | Automatic engine-off
function | Telematics interface | Working lights | Rotating beacon |
Bonnet with electrical easy access engine cover release | Coming home
lighting | Battery isolating switch | Homologation | Tool kit

