

1 HAN

H264

Technical data HD 14i TT

Tandem rollers Series HD CompactLineTandem roller with two sets of wheels

HIGHLIGHTS

- > Easy transport, simple loading
- > Ergonomic driver platform
- > Simple, intuitive and language-neutral operation
- > Compact dimensions
- > Excellent view of the tyres, the machine and the construction site

TECHNICAL DATA HD 14i TT (H264)

Weights 3845 Operating weight with cab kq 3545 Operating weight with ROPS kg Empty weight without cab, 3205 kq without ROPS 4400 Maximum operating weight kg Axle load, front/rear 1680/1865 kg French classification, 5,6/PLO value/class Wheel load per tyre, 560/466,25 kg front/rear Machine dimensions Total length 2965 mm Total height with cab 2720 mm Total height with ROPS 2590 mm Height loading, min. 1820 mm 1950 Centre distance mm Total width 1296 mm Maximum working width 1276 mm Ground clearance, centre 305 mm Kerb clearance, left/right -/mm Turning radius, inside mm 2602 Tyre dimensions Size of tyres, front/rear 10.5/80-16 Width over tyres, front/rear 1127/1276 mm Number of tyres, front/rear 3/4 **Diesel engine** Manufacturer Kubota Model V2403-CR-E5B Cylinders, quantity 4 Power ISO 14396, kW/PS/rpm 36,8/50,0/2700 Power SAE J1995, kW/HP/rpm 37,4/50,1/2700 EU Stage V / EPA Tier 4 Exhaust emission standard DOC-DPF Exhaust gas after-treatment

Travel drive		
Speed, infinitely variable	km/h	0-10,0
Gradeability	%	40
Steering		
Pendulum angle +/-	0	8
Steering, type		Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capacity		
Fuel tank, capacity	L	70
r der tarint, capacity	L	73
Water tank, capacity	L	260
	_	
Water tank, capacity	L	260
Water tank, capacity Additive tank, capacity	L	260

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weatherresistant | Left/right handrails | Battery isolation switch | Pressure water sprinkling system | Driver's platform with access from both sides | Hydrostatic steering | Vibration-isolated driver's platform | CompactLine front towing eye | Lighting package for driving on public roads

OPTIONAL EQUIPMENT

ROPS cab with heating | ROPS, folding | Driver's seat with seat heating, black imitation leather, comfort equipment | Seat belt monitoring device | Radio | Tarpaulin protective roof on ROPS | Thermal aprons | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Engine hood with sound insulation | Water tank cover, lockable | Water drain valve | Tow hitch | Tool kit

HAMM AG • Hammstr. 1 • D-95643 Tirschenreuth • Tel +49 9631 80-0 • Fax +49 9631 80-111 • www.hamm.eu Further data on request/subject to change Illustrations may contain optional features.© Hamm AG 2024 - 2831244 en-GB V7