

# Technical data HD 14i TT

Tandem rollers Series HD CompactLine Tandem roller with two sets of wheels H264

W HAM

НАММ

### **HIGHLIGHTS**

- > Simple transport, simple loading
- > Ergonomic driver platform
- > Simple, intuitive and language-neutral control
- > Compact dimensions
- > Excellent view of tires, machine and construction site

## TECHNICAL DATA HD 14i TT (H264)

Weights		
Operating weight with cab	kg Ibs	3845 8,478
Operating weight with ROPS	kg Ibs	3545 7,817
Empty weight without cab, without ROPS	kg Ibs	3205 7,067
Maximum operating weight	kg	4400 9,702
Axle load, front/rear	kg	1680/1865 3,704/4,112
French classification, value/class	105	5,6/PLO
Wheel load per tire, front/rear	kg	560/466,25
Machine dimensions	lbs	1,235/1,028
Total length	mm	2965
Total height with cab	in mm	116.7 2720
Total height with ROPS	in mm	107.1
Total height with ROPS	in	102.0
Height loading, min.	mm in	1820 71.7
Center distance	mm in	1950 76.8
Total width	mm in	1296 51.0
Maximum working width	mm in	1276 50.2
Ground clearance, center	mm in	305 12.0
Curb clearance, left/right	mm in	-/- -/-
Turning radius, inside	mm in	2602 102.4
Tire dimensions		
Size of tires, front/rear		10.5/80-16
Width over tires, front/rear	mm in	1127/1276 44.4/50.2
Number of tires, front/rear		3/4
Diesel engine		
Manufacturer		Kubota
Model		V2403-CR-E5B
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		36,8/50,0/2700
Power SAE J1995, kW/HP/rpm		37,4/50,1/2700
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF
Travel drive		
Speed, infinitely variable	km/h mph	0-10,0 0.0-6.2
Gradeability	%	40

0	8		
	Articulated steering		
Water-sprinkling system			
	Pressure		
Tank capacity/filling capacity			
L Gal	73 19.3		
L Gal	260 68.7		
L Gal	18 4.8		
Sound level			
db(A)	101		
db(A)	99		
	ty L Gal L Gal L Gal db(A)		

#### EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weatherresistant | Left/right handrails | Battery isolation switch | Pressure water sprinkling system | Driver's platform with access from both sides | Hydrostatic steering | Vibration-isolated driver's platform | CompactLine front towing eye | Lighting package for driving on public roads

#### **OPTIONAL EQUIPMENT**

ROPS cab with heating | ROPS, folding | Driver's seat with seat heating, black imitation leather, comfort equipment | Seat belt monitoring device | Radio | Tarpaulin protective roof on ROPS | Thermal aprons | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Engine hood with sound insulation | Water tank cover, lockable | Water drain valve | Tow hitch | Tool kit

WIRTGEN AMERICA • 6030 Dana Way • Antioch, TN 37013 • Phone +1 615-501-0600 • Fax +1 615-501-0691 • info.america@wirtgen-group.com • www.wirtgen-group.com/america

HAMM AG • Hammstr. 1 • D-95643 Tirschenreuth • Tel +49 9631 80-0 • Fax +49 9631 80-111 • www.hamm.eu

Further data on request/subject to change Illustrations may contain optional features.© Hamm AG 2024 - 2831244 en-US V7



