

Technical data

HC 180 P



Compactors Series HC
Compactor with padfoot drum

H257

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 180 P (H257)

Weights

Operating weight with cab	kg lbs	16715 36,857
Operating weight with ROPS	kg lbs	16495 36,371
Empty weight without cab, without ROPS	kg lbs	15630 34,464
Max. operating weight	kg lbs	18120 39,955
Axle load, front/rear	kg lbs	11100/5615 24,475/12,381
Axle load at max. operating weight, front/rear	kg lbs	12180/6240 26,857/13,759
Static linear load, front	kg/cm lbs/in	51,87 290.5
French classification, value/class		73,48/VPM5
Wheel load per tire, rear	kg lbs	2807,5 6,191

Machine dimensions

Total length	mm in	6527 257.0
Total height with cab	mm in	3046 119.9
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3267 128.6
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	425 16.7
Curb clearance, left/right	mm in	462/462 18.2/18.2
Turning radius, inside	mm in	4137 162.9
Slope angle, front/rear	°	31,6/25,7

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1697 66.8
Drum thickness, front	mm in	30 1.2
Drum type, front		Padfoot
Height of the padfeet	mm in	112 4.4
Padfeet, quantity		130

Tire dimensions

Tire size, rear		TR 23.1/18-26 12 PR
-----------------	--	---------------------

Tire dimensions

Width over tires, rear	mm in	2140 84.3
Number of tires, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 2012 L06 2V
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		150,0/203,9/2000
Power SAE J1349, kW/HP/rpm		150,0/201,2/2000
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

Travel drive

Speed, infinitely variable	km/h mph	0 - 12,0 0.0 - 7.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	55/61

Vibration

Vibration frequency, front, level I/II	Hz vpm	28/31 1,680/1,860
Amplitude, front, level I/II	mm in	2,15/1,35 .085/.053
Centrifugal force, front, level I/II	kN lbs	330/260 74,250/58,500

Steering

Steering angle +/-	°	35
Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	336 88.8
---------------------	----------	-------------

Sound level

Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, manual | Steel scraper, for padfoot drum

OPTIONAL EQUIPMENT