

Technical data

# HX 70i VV-S



**Tandem rollers Series HX**

Tandem roller with two vibrating roller drums

**H297**

**HIGHLIGHTS**

- > High compaction quality through optimum setting of the compaction parameters
- > Intelligent water sprinkler system
- > Operating concept Easy Drive
- > Innovative cabin concept for optimal visibility and high comfort
- > Digital ready

## TECHNICAL DATA HX 70i VV-S (H297)

## Weights

Operating weight with cab	kg	7970
Empty weight without cab, without ROPS	kg	6960
Maximum operating weight	kg	10500
Axle load, front/rear	kg	3990/3980
Axle load at maximum operating weight, front/rear	kg	3560/6940
Static linear load, front/rear	kg/cm	26,60/26,54
French classification, value/class		19,9/VT0

## Machine dimensions

Total length	mm	4140
Total height with cab	mm	2960
Height loading, min.	mm	2170
Centre distance	mm	3000
Total width with cab	mm	1680
Maximum working width	mm	2770
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	610/610
Turning radius, inside	mm	2800

## Drum dimensions

Drum width, front/rear	mm	1500/1500
Drum diameter, front/rear	mm	1140/1140
Drum thickness, front/rear	mm	17/17
Drum type, front		Smooth/split
Drum type, rear		Smooth/split
Track offset, left/right	mm	1270

## Diesel engine

Manufacturer		Kubota
Model		V3307-CR-TE5AB
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		54,6/74,3/2200
Power SAE J1349, kW/HP/rpm		55,4/74,2/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

## Travel drive

Speed, infinitely variable	km/h	0-12,0
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	37/41

## Vibration

Vibration frequency, front, I/II	Hz	42/50
Vibration frequency, rear, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,58/0,40
Amplitude, rear, I/II	mm	0,58/0,40
Centrifugal force, front, I/II	kN	63,23/62,57
Centrifugal force, rear, I/II	kN	63,23/62,57

## Steering

Pendulum angle +/-	°	4
Steering, type		All-wheel, analogue

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	148
Water tank, capacity	L	740

## Sound level

Sound power level L(WA), guaranteed	db(A)	104
Sound power level L(WA), representative measurement	db(A)	103

## EQUIPMENT

Scrapers foldable | Easy Drive operating concept | Pressure water sprinkling system | ECO mode | Frequency control | Speed preselect | Track offset, hydraulic | Automatic vibration system | Water filter system (3-fold) | Central water outlet | Camera system, front and rear | Working spotlights

## OPTIONAL EQUIPMENT

ROPS cab with split doors | Heating and air-conditioning system | Tachograph | Bluetooth interface for Smart Doc | | Smart Compact | Weather station | | Edge pressing and cutting equipment | Chip spreader | HAMM Compaction Meter (HCM) | Speedometer | Automatic engine stop | HAMM Temperature Meter (HTM) | Back-up alarm | JDLINK | Drum edge lighting | Drum lighting | Coming Home function