

Technical data

# HX 70i VS-OS



## Tandem rollers Series HX

Tandem roller with vibration and oscillation drum

H297

### HIGHLIGHTS

- > Compaction with oscillation
- > Intelligent water sprinkler system
- > Operating concept Easy Drive
- > Innovative cabin concept for optimal visibility and high comfort
- > Digital ready

## TECHNICAL DATA HX 70i VS-OS (H297)

## Weights

Operating weight with cab	kg	8400
Empty weight without cab, without ROPS	kg	7390
Max. operating weight	kg	10930
Axle load, front/rear	kg	3990/4410
Max. axle load, front/rear	kg	3560/7370
Static linear load, front/rear	kg/cm	26,60/29,28
French classification, value/class		20,8/VT1

## Machine dimensions

Total length	mm	4140
Total height with cab	mm	2960
Height loading, min.	mm	2170
Centre distance	mm	3000
Total width with cab	mm	1680
Maximum working width	mm	2770
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	610/610
Turning radius, inside	mm	2800

## Drum dimensions

Drum width, front/rear	mm	1500/1500
Drum diameter, front/rear	mm	1140/1140
Drum thickness, front/rear	mm	17/20
Drum type, front		Smooth/split
Drum type, rear		Smooth/split
Track offset, left/right	mm	1270

## Diesel engine

Manufacturer		Kubota
Model		V3307-CR-TE5B
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2200
Power SAE J1349, kW/HP/rpm		55,4/74,3/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

## Travel drive

Speed, infinitely variable	km/h	0 - 12,0
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	35/39

## Vibration

Vibration frequency, front, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,58/0,40
Centrifugal force, front, I/II	kN	63,23/62,57

## Oscillation

Oscillation force, rear	kN	108,26
Oscillation frequency, rear	Hz	36
Tangential amplitude, rear	mm	1,11

## Steering

Swing angle +/-	°	4
Steering, type		All-wheel, analogue

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	148
Water tank, capacity	L	740

## Sound level

Sound power level L(WA), guaranteed	db(A)	104
Sound power level L(WA), representative measurement	db(A)	104

## EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | Folding scraper | Easy Drive operating concept | Pressure refuelling of water from below | Pressure water sprinkling system | ECO mode | Driver's platform with entry from both sides | Frequency control | Speed-controlled water sprinkling | Speed preselect | Viewing pane, front and rear | Vibration-isolated driver's platform | Track offset, hydraulic | Automatic vibration system | Water-sprinkling system with spray bars front and rear | Water filter system (3-fold) | Water tank front and rear, can be filled from both sides | Central water outlet | Working lights

## OPTIONAL EQUIPMENT

ROPS cabin with split doors | Heating and air conditioning | Tachograph | HCQ Navigator | Edge pressing and cutting equipment | Chip spreader | Speedometer | Automatic engine-off function | HAMM Temperature Meter (HTM) | Back-up alarm (reversing) | Drum edge lighting | Drum lighting | Coming home lighting | Bluetooth interface for Smart Doc |