

Technical data

HC 130i C



Compactors Series HC
Compactor with smooth drum

H254

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 130i C (H254)

Weights

Operating weight with cab	kg	13365
Operating weight with ROPS	kg	13015
Empty weight without cab, without ROPS	kg	12290
Max. operating weight	kg	17800
Axle load, front/rear	kg	7840/5525
Axle load at max. operating weight, front/rear	kg	8570/9230
Static linear load, front	kg/cm	36,64
French classification, value/class		50,95/VM3
Wheel load per tyre, rear	kg	2762,5

Machine dimensions

Total length	mm	6117
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	34,2/23,7

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1504
Drum thickness, front	mm	30
Drum type, front		Smooth

Tyre dimensions

Tyre size, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2122
Number of tyres, rear		2

Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PSS
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		119,6/162,6/2000
Power SAE J1349, kW/HP/rpm		119,6/160,4/2000
Exhaust emissions category, EU		EU Stage 5
Exhaust emissions category, USA		EPA Tier 4
Exhaust emissions category, Korea		KOR Stage 5
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h	0 - 12,1
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	57/63

Vibration

Vibration frequency, front, level I/II	Hz	30/36
Amplitude, front, level I/II	mm	2,05/1,1
Centrifugal force, front, level I/II	kN	290/220

Steering

Steering angle +/-	°	35
Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L	280
AdBlue/SCR reducing agent tank, capacity	L	32

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Working spotlights

OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Auxiliary heater | Tachograph | Bluetooth interface for Smart Doc | Smart Receiver | Padfoot shells | Vibration plate | Back-up alarm | Coming Home function | Automatic engine stop | Battery isolation switch