

Technical data

# HC 160i P



**Compactors Series HC**  
Compactor with padfoot drum

**H254**

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**P**

## TECHNICAL DATA HC 160i P (H254)

## Weights

Operating weight with cab	kg	16420
Operating weight with ROPS	kg	16200
Empty weight without cab, without ROPS	kg	15345
Max. operating weight	kg	17550
Axle load, front/rear	kg	11240/5180
Axle load at max. operating weight, front/rear	kg	12150/5600
Static linear load, front	kg/cm	52,52
French classification, value/class		74,48/VPM5
Wheel load per tyre, rear	kg	2590

## Machine dimensions

Total length	mm	6315
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Total height with plastic protective roof	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	33,7/23,7

## Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1697
Drum thickness, front	mm	30
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

## Tyre dimensions

Tyre size, rear		TR 23.1/18-26 12 PR
Width over tyres, rear	mm	2154
Number of tyres, rear		2

## Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PSS
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		119,6/162,6/2000
Power SAE J1349, kW/HP/rpm		119,6/160,4/2000
Exhaust emissions category, EU		EU Stage 5
Exhaust emissions category, USA		EPA Tier 4
Exhaust emissions category, Korea		KOR Stage 5
Exhaust gas after-treatment		DOC-DPF-SCR

## Travel drive

Speed, infinitely variable	km/h	0 - 11,9
----------------------------	------	----------

## Travel drive

Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	55/61

## Vibration

Vibration frequency, front, level I/II	Hz	28/31
Amplitude, front, level I/II	mm	2,15/1,35
Centrifugal force, front, level I/II	kN	330/260

## Steering

Steering angle +/-	°	35
Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

## Tank capacity/filling capacity

Fuel tank, capacity	L	280
AdBlue/SCR reducing agent tank, capacity	L	32

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

## EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

## OPTIONAL EQUIPMENT

ROPS cab with heating and air-conditioning system (FOPS, level I) | Auxiliary heater | Tachograph | Bluetooth interface for Smart Doc | Smart Receiver | Back-up alarm | Working spotlights | Coming Home function | Automatic engine stop | Battery isolation switch