

Technical data

# HC 130i C P



**Compactors Series HC**  
Compactor with padfoot drum

**H254**

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**P**

## TECHNICAL DATA HC 130i C P (H254)

## Weights

|                                                   |                 |                            |
|---------------------------------------------------|-----------------|----------------------------|
| Operating weight with cab                         | kg<br>lbs       | 13580<br>29,944            |
| Operating weight with ROPS                        | kg<br>lbs       | 13230<br>29,172            |
| Empty weight without cab,<br>without ROPS         | kg<br>lbs       | 12505<br>27,574            |
| Max. operating weight                             | kg<br>lbs       | 15520<br>34,222            |
| Axle load, front/rear                             | kg<br>lbs       | 8280/5300<br>18,257/11,686 |
| Axle load at max. operating<br>weight, front/rear | kg<br>lbs       | 9350/6170<br>20,617/13,605 |
| Static linear load, front                         | kg/cm<br>lbs/in | 38,69<br>216.7             |
| French classification,<br>value/class             |                 | 52,11/VPM3                 |
| Wheel load per tire, rear                         | kg<br>lbs       | 2650<br>5,843              |

## Machine dimensions

|                                              |          |                      |
|----------------------------------------------|----------|----------------------|
| Total length                                 | mm<br>in | 6117<br>240.8        |
| Total height with cab                        | mm<br>in | 3054<br>120.2        |
| Total height with ROPS                       | mm<br>in | 3054<br>120.2        |
| Total height with plastic<br>protective roof | mm<br>in | 3054<br>120.2        |
| Height loading, min.                         | mm<br>in | 3054<br>120.2        |
| Center distance                              | mm<br>in | 3266<br>128.6        |
| Total width with cab                         | mm<br>in | 2474<br>97.4         |
| Maximum working width                        | mm<br>in | 2140<br>84.3         |
| Ground clearance, center                     | mm<br>in | 461<br>18.1          |
| Curb clearance, left/right                   | mm<br>in | 477/477<br>18.8/18.8 |
| Turning radius, inside                       | mm<br>in | 4131<br>162.6        |
| Slope angle, front/rear                      | °        | 33,7/23,7            |

## Drum dimensions

|                       |          |              |
|-----------------------|----------|--------------|
| Drum width, front     | mm<br>in | 2140<br>84.3 |
| Drum diameter, front  | mm<br>in | 1707<br>67.2 |
| Drum thickness, front | mm<br>in | 20<br>0.8    |
| Drum type, front      |          | Padfoot      |
| Height of the padfeet | mm<br>in | 112<br>4.4   |
| Padfeet, quantity     |          | 130          |

## Tire dimensions

|                        |          |                     |
|------------------------|----------|---------------------|
| Tire size, rear        |          | TR 23.1/18-26 12 PR |
| Width over tires, rear | mm<br>in | 2154<br>84.8        |
| Number of tires, rear  |          | 2                   |

## Diesel engine

|                                      |  |                  |
|--------------------------------------|--|------------------|
| Manufacturer                         |  | JOHN DEERE       |
| Model                                |  | JDPS 4045PSS     |
| Cylinders, quantity                  |  | 4                |
| Power ISO 14396, kW/PS/rpm           |  | 119,6/162,6/2000 |
| Power SAE J1349, kW/HP/rpm           |  | 119,6/160,4/2000 |
| Exhaust emissions category,<br>EU    |  | EU Stage 5       |
| Exhaust emissions category,<br>USA   |  | EPA Tier 4       |
| Exhaust emissions category,<br>Korea |  | KOR Stage 5      |
| Exhaust gas after-treatment          |  | DOC-DPF-SCR      |

## Travel drive

|                                         |             |                       |
|-----------------------------------------|-------------|-----------------------|
| Speed, infinitely variable              | km/h<br>mph | 0 - 12,0<br>0.0 - 7.5 |
| Regulation, infinitely variable         |             | HAMMTRONIC            |
| Gradeability, with/without<br>vibration | %           | 59/66                 |

## Vibration

|                                           |           |                          |
|-------------------------------------------|-----------|--------------------------|
| Vibration frequency, front,<br>level I/II | Hz<br>vpm | 30/36<br>1,800/2,160     |
| Amplitude, front, level I/II              | mm<br>in  | 1,90/1,05<br>.075/.041   |
| Centrifugal force, front, level<br>I/II   | kN<br>lbs | 290/220<br>65,250/49,500 |

## Steering

|                    |   |                      |
|--------------------|---|----------------------|
| Steering angle +/- | ° | 35                   |
| Pendulum angle +/- | ° | max. 12              |
| Steering, type     |   | Articulated steering |

## Tank capacity/filling capacity

|                                             |          |             |
|---------------------------------------------|----------|-------------|
| Fuel tank, capacity                         | L<br>Gal | 280<br>74.0 |
| AdBlue/SCR reducing agent<br>tank, capacity | L<br>Gal | 32<br>8.5   |

## Sound level

|                                                        |       |     |
|--------------------------------------------------------|-------|-----|
| Sound power level L(WA),<br>guaranteed                 | db(A) | 106 |
| Sound power level L(WA),<br>representative measurement | db(A) | 103 |

## EQUIPMENT