

Technical data

HC 130 C



Compactors Series HC
Compactor with smooth drum

H255

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 130 C (H255)

Weights

Operating weight with cab	kg lbs	12920 28,489
Operating weight with ROPS	kg lbs	12800 28,224
Basic weight no cab, without ROPS	kg lbs	11980 26,416
Operating weight, max.	kg lbs	17350 38,257
Axle load, front/rear	kg lbs	7650/5270 16,868/11,620
Axle load max., front/rear	kg lbs	8380/8970 18,478/19,779
Static linear load, front	kg/cm lbs/in	35,75 200.2
French classific., data/class		49,71/VM3
Load per tire, rear	kg lbs	2635 5,810

Machine dimensions

Total length	mm in	6117 240.8
Total height with cab	mm in	3054 120.2
Total height with ROPS	mm in	3054 120.2
Height, loading, min.	mm in	3054 120.2
Wheelbase	mm in	3266 128.6
Total width with cab	mm in	2474 97.4
Max. working width	mm in	2140 84.3
Ground clearance, center	mm in	461 18.1
Curb clearance, left/right	mm in	477/477 18.8/18.8
Turning radius, inside	mm in	4131 162.6
Angle of driving slope, front/rear	°	34,2/23,7

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1504 59.2
Drum thickness, front	mm in	30 1.2
Drum type, front		Smooth

Wheel dimensions

Size of tires, rear		AW 23.1-26 12 PR
Width over tires, rear	mm in	2122 83.5
Number of tires, rear		2

Diesel engine

Type		JDPS 4045PTE
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		101,0/137,3/2000
Power rating SAE J1349, kW/HP/rpm		101,0/135,4/2000
Emission standard		EU Stage IIIA/EPA Tier 3
Emissions standard		UN ECE R96
Exhaust gas after-treatment		-

Drive

Speed, infinitely variable	km/h mph	0 - 12,0 0.0 - 7.5
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	57/63

Vibration

Vibration frequency, front, I/II	Hz vpm	30/36 1,800/2,160
Amplitude, front, I/II	mm in	2,05/1,10 .081/.043
Centrifugal force, front, I/II	kN lbs	290/220 65,250/49,500

Steering

Oscillation angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L Gal	280 74.0
---------------------	----------	-------------

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power L(WA), measured	db(A)	104

EQUIPMENT

12 V outlets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Vibration-isolated operator's platform | Automatic vibration system | Plastic scraper, for smooth drum

OPTIONAL EQUIPMENT

ROPS cabin with heating and air conditioning, FOPS-approved (level I) | Safety belt monitoring device | Auxiliary heater | Radio | Tachograph | Bluetooth interface for Smart Doc | Dozer blade | Padfoot shell | Vibration plate | Automatic engine-off function | Camera system | JDLink | Working light | Engine hood with electrical easy access engine cover release | Coming home lighting