

Technical data

HD 18 VV



Tandem rollers Series HD CompactLine

「andem roller with two vibrating roller drums

H292

HIGHLIGHTS

- > Simple, intuitive and language-neutral operation
- > Clear Side one-sided drum suspension
- > Easy transport, simple loading
- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings

TECHNICAL DATA HD 18 VV (H292)

Weights		
Operating weight with ROPS	kg	1590
Empty weight without cab, without ROPS	kg	1420
Max. operating weight	kg	1880
Axle load, front/rear	kg	765/825
Static linear load, front/rear	kg/cm	9,6/10,3
French classification, value/class		10,3/PV3
Machine dimensions		
Total length	mm	2295
Total height with ROPS	mm	2210
Height loading, min.	mm	1580
Centre distance	mm	1560
Total width	mm	938
Maximum working width	mm	872
Ground clearance, centre	mm	230
Turning radius, inside	mm	2230
Drum dimensions		
Drum width, front/rear	mm	800/800
Drum diameter, front/rear	mm	620/620
Drum thickness, front/rear	mm	12/12
Drum type, front	******	Smooth/non-split
Drum type, rear		Smooth/non-split
Diesel engine		Sillooti ii iloii spiit
Manufacturer		Kubota
Model		D1105-E4B
Cylinders, quantity		3
		_
Power SAE 11340, kW/PS/rpm		16,1/21,9/2600 16,1/21,6/2600
Power SAE J1349, kW/HP/rpm Exhaust emission standard		, ,
		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration Vibration frequency, front, I/II	Hz	61/48
Vibration frequency, front, I/II Vibration frequency, rear, I/II	Hz Hz	61/48 61/48
Vibration frequency, front, I/II		
Vibration frequency, front, I/II Vibration frequency, rear, I/II	Hz	61/48
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II	Hz mm	61/48 0,43/0,43
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II	Hz mm mm	61/48 0,43/0,43 0,43/0,43
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II	Hz mm mm kN	61/48 0,43/0,43 0,43/0,43 17/11
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II	Hz mm mm kN	61/48 0,43/0,43 0,43/0,43 17/11
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II Steering	Hz mm mm kN kN	61/48 0,43/0,43 0,43/0,43 17/11 17/11
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II Steering Swing angle +/-	Hz mm mm kN kN	61/48 0,43/0,43 0,43/0,43 17/11 17/11
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II Steering Swing angle +/- Steering, type	Hz mm mm kN kN	61/48 0,43/0,43 0,43/0,43 17/11 17/11
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II Steering Swing angle +/- Steering, type Water-sprinkling system	Hz mm mm kN kN	61/48 0,43/0,43 0,43/0,43 17/11 17/11 8 Articulated steering
Vibration frequency, front, I/II Vibration frequency, rear, I/II Amplitude, front, I/II Amplitude, rear, I/II Centrifugal force, front, I/II Centrifugal force, rear, I/II Steering Swing angle +/- Steering, type Water-sprinkling system Water sprinkling, type	Hz mm mm kN kN	61/48 0,43/0,43 0,43/0,43 17/11 17/11 8 Articulated steering

Sound level		
Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	101

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling system | Driver's platform with entry from both sides | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket | Plastic scraper, folding | Driver's seat in black imitation leather | Technical documentation

OPTIONAL EQUIPMENT

Protective roof | Back-up alarm | Working spotlights | Rotating beacon | Tool kit

