

Technical data

HD+ 110i VV



Tandem rollers Series HD+

Tandem roller with two vibrating roller drums

H303

HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat operating unit can be moved and rotated
- > Digital ready

TECHNICAL DATA HD+ 110i VV (H303)

Weights

Operating weight with cab	kg	10400
Operating weight with ROPS	kg	10220
Empty weight without cab, without ROPS	kg	9410
Max. operating weight	kg	13050
Axle load, front/rear	kg	5285/5115
Static linear load, front/rear	kg/cm	31,46/30,45
French classification, value/class		28,69/VT2

Machine dimensions

Total length	mm	4900
Total height with cab	mm	2980
Total height with ROPS	mm	3030
Height loading, min.	mm	2150
Centre distance	mm	3700
Total width with cab	mm	1800
Maximum working width	mm	1850
Ground clearance, centre	mm	340
Kerb clearance, left/right	mm	800/800
Turning radius, inside	mm	6050

Drum dimensions

Drum width, front/rear	mm	1680/1680
Drum diameter, front/rear	mm	1200/1200
Drum thickness, front/rear	mm	22/22
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	170

Diesel engine

Manufacturer		DEUTZ
Model		TCD 3.6 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		85,0/115,6/2300
Power SAE J1349, kW/HP/rpm		85,0/113,9/2300
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h	0 - 10,4
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	37/41

Vibration

Vibration frequency, front, I/II	Hz	42/50
Vibration frequency, rear, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,90/0,50
Amplitude, rear, I/II	mm	0,90/0,50
Centrifugal force, front, I/II	kN	120/100
Centrifugal force, rear, I/II	kN	120/100

Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L	173
AdBlue/SCR reducing agent tank, capacity	L	20
Water tank, capacity	L	760

Sound level

Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	103

EQUIPMENT

12 V power socket | Two large exterior rear-view mirrors | Folding scraper | Easy Drive operating concept | Pressure water sprinkling system | ECO mode | Driver's platform with entry from both sides | Speed-controlled water sprinkling | Speed preselect | Automatic traction control and anti-slip control | Vibration-isolated driver's platform | Water-sprinkling system with spray bars front and rear | Track offset, hydraulic | Water filter system (3-fold) | Water tank front and rear, can be filled from both sides | Central water outlet | Additive-sprinkling system for tyres, rear | Steering column with tilttable dashboard

OPTIONAL EQUIPMENT

Heating and air-conditioning system | Tachograph | Process data interface for third-party provider systems, asphalt construction | Bluetooth interface for Smart Doc | | Smart Compact | Weather station | | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Camera system | JDLink | Working spotlights | Drum edge lighting | Coming Home function