

Technical data

# HD+ 140i VO



## Tandem rollers Series HD+

Tandem roller with vibration and oscillation drum

H304

### HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Compaction with oscillation
- > Digital ready

## TECHNICAL DATA HD+ 140i VO (H304)

## Weights

Operating weight with cab	kg lbs	13120 28,930
Operating weight with ROPS	kg lbs	12890 28,422
Empty weight without cab, without ROPS	kg lbs	11805 26,030
Max. operating weight	kg lbs	14140 31,179
Axle load, front/rear	kg lbs	6475/6645 14,277/14,652
Static linear load, front/rear	kg/cm lbs/in	30,26/31,05 169.4/173.9
French classification, value/class		28,23/VT2

## Machine dimensions

Total length	mm in	5300 208.7
Total height with cab	mm in	2980 117.3
Total height with ROPS	mm in	3030 119.3
Height loading, min.	mm in	2140 84.3
Center distance	mm in	3900 153.5
Total width with cab	mm in	2260 89.0
Maximum working width	mm in	2310 90.9
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	900/900 35.4/35.4
Turning radius, inside	mm in	6200 244.1

## Drum dimensions

Drum width, front/rear	mm in	2140/2140 84.3/84.3
Drum diameter, front/rear	mm in	1400/1400 55.1/55.1
Drum thickness, front/rear	mm in	19/19 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	170 6.7

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 4.1 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		115,0/156,4/2300
Power SAE J1349, kW/HP/rpm		115,0/154,1/2300
Exhaust emission standard		EU Stage V / EPA Tier 4

## Diesel engine

Exhaust gas after-treatment		DOC-DPF-SCR
-----------------------------	--	-------------

## Travel drive

Speed, infinitely variable	km/h mph	0-10,5 0.0-6.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	37/41

## Vibration

Vibration frequency, front, I/II	Hz vpm	40/50 2,400/3,000
Amplitude, front, I/II	mm in	0,90/0,35 .035/.014
Centrifugal force, front, I/II	kN lbs	160/95 36,000/21,375

## Oscillation

Oscillation force, rear	kN lbs	170,48 38,358
Oscillation frequency, rear	Hz vpm	36 2,160
Tangential amplitude, rear	mm in	1,10 .043

## Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L Gal	260 68.7
AdBlue/SCR reducing agent tank, capacity	L Gal	20 5.3
Water tank, capacity	L Gal	1145 302.5

## Sound level

Sound power level L(WA), guaranteed	db(A)	109
Sound power level L(WA), representative measurement	db(A)	107

## EQUIPMENT

Heating and air-conditioning system | Steering column with comfort exit and tiltable dashboard | Tachograph | Process data interface for third-party provider systems, asphalt construction | Bluetooth interface for Smart Doc | | Smart Compact | Weather station | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Camera system | JDLink | Working spotlights | Drum edge lighting | Coming Home function

## OPTIONAL EQUIPMENT