

**Technical data** 

# HD 8 VV



Tandem rollers Series HD CompactLine

Fandem roller with two vibrating roller drums

H263

## **HIGHLIGHTS**

- > Simple, intuitive and language-neutral operation
- > Clear Side one-sided drum suspension
- > Easy transport, simple loading
- > Compact dimensions
- > Excellent view of the drum edges, the machine and the construction site surroundings

HD 8 VV | **TECHNICAL DATA** 

### **TECHNICAL DATA HD 8 VV (H263)**

Weights		
Operating weight with ROPS	kg	1590
Maximum operating weight	kg	1690
Static linear load, front/rear	kg/cm	9,6/10,3
French classification, value/class	g. s	10,3/PV3
Machine dimensions		
Total length	mm	2295
Total height with ROPS	mm	2210
Height loading, min.	mm	1580
Centre distance	mm	1560
Total width	mm	938
Maximum working width	mm	872
Ground clearance, centre	mm	230
Turning radius, inside	mm	2230
Drum dimensions		
Drum width, front/rear	mm	800/800
Drum diameter, front/rear	mm	620/620
Drum thickness, front/rear	mm	12/12
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Diesel engine		
Manufacturer		Kubota
Model		D1105-E4B
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		16,1/21,9/2600
Power SAE J1349, kW/HP/rpm		16,1/21,6/2600
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust emissions category, EU		EU Stage V
Exhaust emissions category, USA		EPA Tier 4
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, I/II	Hz	61/48
Vibration frequency, rear, I/II	Hz	61/48
Amplitude, front, I/II	mm	0,43/0,43
Amplitude, rear, I/II	mm	0,43/0,43
Centrifugal force, front, I/II	kN	17/11
Centrifugal force, rear, I/II	kN	17/11
Steering		
Pendulum angle +/-	٥	8
Steering, type		Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capaci	ty	
Fuel tank, capacity	L	33
Water tank, capacity	L	70

Sound level		
Sound power level L(WA), guaranteed	db(A)	105
Sound power level L(WA), representative measurement	db(A)	100

### **EQUIPMENT**

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling system | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

### **OPTIONAL EQUIPMENT**

Plastic scraper, folding | Additional drive lever, left | Protective roof | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Battery isolation switch | Engine hood with sound insulation | Water drain valve | Tool kit

