

Technical data

HD 10C VT



Tandem rollers Series HD CompactLine

Tandem roller with vibration drum and set of wheels

H263

HIGHLIGHTS

- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Clear Side — one-sided drum suspension
- > Compact dimensions
- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation

TECHNICAL DATA HD 10C VT (H263)

Weights

| | | |
|------------------------------------|-------|---------|
| Operating weight with ROPS | kg | 1640 |
| Max. operating weight | kg | 1740 |
| Static linear load, front | kg/cm | 8,1 |
| French classification, value/class | | 8,1/PV1 |

Machine dimensions

| | | |
|------------------------|----|------|
| Total length | mm | 2309 |
| Total height with ROPS | mm | 2210 |
| Height loading, min. | mm | 1580 |
| Centre distance | mm | 1560 |
| Total width | mm | 1070 |
| Maximum working width | mm | 1000 |
| Turning radius, inside | mm | 2130 |

Drum dimensions

| | | |
|-----------------------|----|------------------|
| Drum width, front | mm | 1000 |
| Drum diameter, front | mm | 620 |
| Drum thickness, front | mm | 12 |
| Drum type, front | | Smooth/non-split |

Tyre dimensions

| | | |
|------------------------|----|------------|
| Tyre size, rear | | 205/60-R15 |
| Width over tyres, rear | mm | 1000 |
| Number of tyres, rear | | 4 |

Diesel engine

| | | |
|-----------------------------------|--|----------------|
| Manufacturer | | KUBOTA |
| Model | | D1105-E4B |
| Cylinders, quantity | | 3 |
| Power ISO 14396, kW/PS/rpm | | 16,1/21,9/2600 |
| Power SAE J1349, kW/HP/rpm | | 16,1/21,6/2600 |
| Exhaust emission standard | | MEE 3 |
| Exhaust emissions category, EU | | EU Stage 5 |
| Exhaust emissions category, USA | | EPA Tier 4 |
| Exhaust emissions category, Korea | | KOR Stage 5 |
| Exhaust gas after-treatment | | - |

Travel drive

| | | |
|--------------------------------------|------|----------|
| Speed, infinitely variable | km/h | 0 - 11,0 |
| Gradeability, with/without vibration | % | 30/40 |

Vibration

| | | |
|--|----|-----------|
| Vibration frequency, front, level I/II | Hz | 61/48 |
| Amplitude, front, level I/II | mm | 0,38/0,38 |
| Centrifugal force, front, level I/II | kN | 17/11 |

Steering

| | | |
|--------------------|---|----------------------|
| Pendulum angle +/- | ° | 8 |
| Steering, type | | Articulated steering |

Water-sprinkling system

| | | |
|------------------------|--|----------|
| Water sprinkling, type | | Pressure |
|------------------------|--|----------|

Tank capacity/filling capacity

| | | |
|-------------------------|---|----|
| Fuel tank, capacity | L | 33 |
| Water tank, capacity | L | 70 |
| Additive tank, capacity | L | 9 |

Sound level

| | | |
|---|-------|-----|
| Sound power level L(WA), guaranteed | db(A) | 105 |
| Sound power level L(WA), representative measurement | db(A) | 100 |

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Clear Side | Pressure water sprinkling system | V-belt protection | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, folding | Equipment Management | Additional drive lever, left | Protective roof | Water drain valve | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Battery isolation switch | Tool kit