

Technical data

# HD+ 80i VV-S



## Tandem rollers Series HD+

Tandem roller with two vibration drums

H302

### HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat-operating unit can be moved and rotated
- > Digital ready

## TECHNICAL DATA HD+ 80i VV-S (H302)

## Weights

Operating weight with cab	kg lbs	8095 17,849
Operating weight with ROPS	kg lbs	7915 17,453
Empty weight without cab, without ROPS	kg lbs	7200 15,876
Max. operating weight	kg lbs	10700 23,593
Axle load, front/rear	kg lbs	4080/4015 8,996/8,853
Static linear load, front/rear	kg/cm lbs/in	24,27/23,89 135.9/133.8
French classification, value/class		17,54/VT0

## Machine dimensions

Total length	mm in	4480 176.4
Total height with cab	mm in	2890 113.8
Total height with ROPS	mm in	2970 116.9
Height loading, min.	mm in	2080 81.9
Center distance	mm in	3340 131.5
Total width with cab	mm in	1800 70.9
Maximum working width	mm in	1815 71.5
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	750/750 29.5/29.5
Turning radius, inside	mm in	4140 163.0

## Drum dimensions

Drum width, front/rear	mm in	1680/1680 66.1/66.1
Drum diameter, front/rear	mm in	1140/1140 44.9/44.9
Drum thickness, front/rear	mm in	17/17 0.7/0.7
Drum type, front		Smooth/split
Drum type, rear		Smooth/split
Track offset, left/right	mm in	135 5.3

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 2.9 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2300
Power SAE J1349, kW/HP/rpm		55,4/74,2/2300
Exhaust emission standard		EU Stage V / EPA Tier 4

## Diesel engine

Exhaust gas after-treatment		DOC-DPF
-----------------------------	--	---------

## Travel drive

Speed, infinitely variable	km/h mph	0 - 10,2 0.0 - 6.3
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	38/42

## Vibration

Vibration frequency, front, level I/II	Hz vpm	42/50 2,520/3,000
Vibration frequency, rear, level I/II	Hz vpm	42/50 2,520/3,000
Amplitude, front, level I/II	mm in	0,55/0,40 .022/.016
Amplitude, rear, level I/II	mm in	0,55/0,40 .022/.016
Centrifugal force, front, level I/II	kN lbs	65/65 14,625/14,625
Centrifugal force, rear, level I/II	kN lbs	65/65 14,625/14,625

## Steering

Pendulum angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L Gal	120 31.7
Water tank, capacity	L Gal	700 184.9

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

## EQUIPMENT

Dashboard tiltable | Pressure water sprinkling system | ECO mode | Speed preselect | Vibration-insulated driver's platform | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

## OPTIONAL EQUIPMENT

ROPS, rigid | Steering column with comfort exit and tiltable dashboard | Protective roof | Tachograph | Bluetooth interface for Smart Doc | Smart Receiver | Edge pressing and cutting device | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | Working spotlights | Rotating beacon