



CHIP SPREADER (SERIES HD+)

TECHNICAL DATA:

Type	Availability	Line spreader	Disc spreader	Spreading width [m]	Storage capacity [l]
HLS 170	HD+ 70i, HD+ 80i, HD+ 90i, HD+ 110i	•		0.30-1.70	960
HDS 18	HD+ 70i, HD+ 80i, HD+ 90i, HD+ 110i		•	1.00-8 (depending on the material)	750

HLS 150 AND HLS 170: AN OVERVIEW (HLS = HAMM LINE SPREADER):

- ◇ One size, suitable for the drum widths of the HD+ 70i (1500 mm) and the HD+ 80i, HD+ 90i, HD+ 110i (1680 mm)
- ◇ Excellent, even spreading pattern
- ◇ Precise spreading width
- ◇ Regulation of spreading quantity: Constant spreading quantity, even when travelling quickly or on an inline
- ◇ Speed-dependent application of chips
- ◇ Convenient, electronic spreading quantity adjustment
- ◇ Great access to hydraulic systems and all maintenance points
- ◇ Convenient attachment thanks to the quick coupling, quick filling
- ◇ Holder with the aid of the forklift pockets or the lifting eyes
- ◇ Bracket (rigid) with three-point mounting bracket and without drum protrusion
- ◇ Rear-view camera (mandatory option)

- ① Convenient spreading width adjustment via five or six segments
- ② Convenient quick emptying
- ③ Self-retracting tarpaulin
- ④ Spotlight with front-grille guard
- ⑤ Rear-view camera for optimum visibility
- ⑥ Forklift pockets for the holder
- ⑦ Lifting eyes inside the container
- ⑧ Spreading plate for a fine spreading pattern



HDS 18 – AN OVERVIEW:

- ◇ Large spreading width
- ◇ Bracket (rigid) with three-point mounting bracket and without drum protrusion
- ◇ Chip quantity application as per preselection
- ◇ Rear-view camera for optimum visibility (required option)
- ◇ Convenient attachment thanks to the quick coupling
- ◇ Convenient quick emptying
- ◇ Made in Germany

