

Technical data

HC 250 C VC



Compactors Series HC

Compactor with vibration crusher drum

H257

HIGHLIGHTS

- > 2 in 1: Crushing and compaction in one operation
- > High crushing force due to high point load
- > Wide range of applications (e.g. road construction, landfill site construction, surface mining, etc.)
- > New toolholder system for simple tool changes
- > Powerful drive, no-spin axle and 3-point articulation for outstanding traction and off-road mobility

TECHNICAL DATA HC 250 C VC (H257)

Weights		
Operating weight with cab	kg lbs	24695 54,452
Max. operating weight	kg lbs	26300 57,991
Axle load, front/rear	kg lbs	17560/7135 38,720/15,733
Axle load at max. operating weight, front/rear	kg lbs	18540/7760 40,881/17,111
Static linear load, front	kg/cm lbs/in	82,06 459.5
French classification, value/class		-
Wheel load per tire, rear	kg lbs	3567,5 7,866

Machine dimensions		
Total length	mm in	6871 270.5
Total height with cab	mm in	3046 119.9
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3553 139.9
Total width with cab	mm in	2496 98.3
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	453 17.8
Curb clearance, left/right	mm in	580/580 22.8/22.8
Turning radius, inside	mm in	4904 193.1
Slope angle, front/rear	°	44,6/25,7

Drum dimensions		
Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1710 67.3
Drum thickness, front	mm in	35 1.4
Drum type, front		VC
Tool holder, quantity		126

Tire dimensions		
Tire size, rear		EM 23.5-25/20PR TL
Width over tires, rear	mm in	2082 82.0
Number of tires, rear		2

Diesel engine		
Manufacturer		DEUTZ
Model		TCD 2012 L06 2V
Cylinders, quantity		6

Diesel engine		
Power ISO 14396, kW/PS/rpm		150,0/203,9/2000
Power SAE J1349, kW/HP/rpm		150,0/201,2/2000
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

Travel drive		
Speed, infinitely variable	km/h mph	0 - 11,8 0.0 - 7.3
Regulation, infinitely variable		HAMMTRONIC/manual
Gradeability, with/without vibration	%	59/66

Steering		
Steering angle +/-	°	35
Pendulum angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/filling capacity		
Fuel tank, capacity	L Gal	336 88.8

Sound level		
Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, automatic | ROPS cab with heating system (FOPS, level I) | Tool insert

OPTIONAL EQUIPMENT

Seat belt monitoring device | Armrest comfort setting, left | Auxiliary heater | Radio | Tachograph | Fire extinguisher | Bluetooth interface for Smart Doc | Dashboard cover | Automatic engine stop | Camera system | Working spotlights | Rotating beacon | Engine hood with electrical release mechanism | Coming Home function | Battery isolation switch | Tool kit