

Technical data

HC 200i C VA



Compactors Series HC
Compactor with VA drum

H256

HIGHLIGHTS

- > High compaction power, efficiency and process reliability
- > Spacious driver's platform with Easy Drive operating concept
- > Precise compaction measurement with new measured value (in MN/m²)
- > Automatic control of compaction using target values
- > Digital ready

TECHNICAL DATA HC 200i C VA (H256)

Weights

Operating weight with cab	kg lbs	20065 44,243
Operating weight with ROPS	kg lbs	19845 43,758
Empty weight without cab, without ROPS	kg lbs	18940 41,763
Max. operating weight	kg lbs	20720 45,688
Axle load, front/rear	kg lbs	13795/6270 30,418/13,825
Axle load at max. operating weight, front/rear	kg lbs	13820/6900 30,473/15,214
Static linear load, front	kg/cm lbs/in	64,46 361.0
French classification, value/class		98,65/VM5
Wheel load per tire, rear	kg lbs	3135 6,913

Machine dimensions

Total length	mm in	6610 260.2
Total height with cab	mm in	3046 119.9
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3312 130.4
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	453 17.8
Curb clearance, left/right	mm in	469/469 18.5/18.5
Turning radius, inside	mm in	4278 168.4
Slope angle, front/rear	°	36,6/25,7

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1600 63.0
Drum thickness, front	mm in	45 1.8
Drum type, front		Smooth

Tire dimensions

Tire size, rear		AW 23.1-26 12 PR
Width over tires, rear	mm in	2140 84.3
Number of tires, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 6.1 L6
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		160,0/217,7/2000
Power SAE J1349, kW/HP/rpm		160,0/214,7/2000
Exhaust emissions category, EU		EU Stage V
Exhaust emissions category, USA		EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h mph	0 - 11,7 0.0 - 7.3
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	56/62

Vibration

Vibration frequency, front	Hz vpm	27 1,620
Amplitude, front, max.	mm in	2,55 .100
Centrifugal force, front, max.	kN lbs	450 101,250

Steering

Steering angle +/-	°	35
Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	336 88.8
AdBlue/SCR reducing agent tank, capacity	L Gal	32 8.5

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, automatic | Plastic scraper, for smooth drum

OPTIONAL EQUIPMENT