

Technical data

# HC 130 C P



**Compactors Series HC**  
Compactor with padfoot drum

**H313**

## HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**P**

## TECHNICAL DATA HC 130 C P (H313)

## Weights

Operating weight with cab	kg	13350
Operating weight with ROPS	kg	13000
Empty weight without cab, without ROPS	kg	12305
Max. operating weight	kg	14800
Axle load, front/rear	kg	8160/5190
Axle load at max. operating weight, front/rear	kg	9230/5570
Static linear load, front	kg/cm	38,13
French classification, value/class		51,44/VPM3
Wheel load per tyre, rear	kg	2595

## Machine dimensions

Total length	mm	6117
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Total height with plastic protective roof	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	33,7/23,7

## Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1707
Drum thickness, front	mm	20
Drum type, front		Padfoot
Height of the padfeet	mm	112
Padfeet, quantity		130

## Tyre dimensions

Tyre size, rear		TR 23.1/18-26 12 PR
Width over tyres, rear	mm	2154
Number of tyres, rear		2

## Diesel engine

Manufacturer		JOHN DEERE
Model		JDPS 4045PTE
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		112/152,3/2200
Power SAE J1349, kW/HP/rpm		112/150,0/2200
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

## Travel drive

Speed, infinitely variable	km/h	0 - 11,6
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	59/66

## Vibration

Vibration frequency, front, level I/II	Hz	30/36
Amplitude, front, level I/II	mm	1,90/1,05
Centrifugal force, front, level I/II	kN	290/220

## Steering

Steering angle +/-	°	35
Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

## Tank capacity/filling capacity

Fuel tank, capacity	L	280
---------------------	---	-----

## Sound level

Sound power level L(WA), guaranteed	db(A)	109
Sound power level L(WA), representative measurement	db(A)	107

## EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system

## OPTIONAL EQUIPMENT

ROPS cab with heating system (FOPS, level I) | Heating / air-conditioning system | Tachograph | Smart Receiver | Process data interface for third-party provider systems, earthworks | Vibration plate | John Deere Operations Center | Working spotlights | Engine hood with electrical release mechanism