

Technical information

MOBISCREEN MSS 352 EVO



Track-mounted screening plant

Use in natural stone and recycling

MOBISCREEN MSS EVO

Series

HIGHLIGHTS

- > Double-deck screening unit
- > Scalping screen
- > Diesel-hydraulic drive
- > Max. feed size: 19" x 12" x 7"

TECHNICAL DATA MSS 352 EVO - US SPEC

Feeding unit	
Feed capacity up to approx. (US t/h)	220
Feed size max. (inch)	19" x 12" x 7"
Feed height (inch)	9' 4"
Hopper capacity (yd ³)	5.2
Feeding conveyor	
Width x length (inch)	3' 11" x 10' 6"
Type (optional)	variable speed
Screening unit	
Type	double-deck screen
Top deck width x length (inch)	4' x 9'
Bottom deck width x length (inch)	4' x 8' 6"
Belt conveyor underflow material	
Width x length (inch)	3' 5" x 7' 3"
Discharge conveyor underflow lower deck (fine grain)	
Width x length (inch)	2' 2" x 23'
Discharge height approx. (inch)	11' 8"
Bottom deck overflow discharge conveyor (medium fractions)	
Width x length (inch)	2' 2" x 22' 12"
Discharge height approx. (inch)	11' 8"
Top deck overflow discharge conveyor (oversize fractions)	
Width x length (inch)	3' 5" x 15' 1"
Discharge height approx. (inch)	11' 2"

Drive	
Drive concept	diesel-hydraulic
Powerpack CAT (Tier 3, 4f) (hp)	127
Powerpack CAT (Stage V) (hp)	134
Transport	
Transport height approx. (inch)	10' 6"
Transport length approx. (inch)	31' 10"
Transport width approx. (inch)	8' 3"
Transport weight approx. (lbs)	34,100

OPERATING POSITION

