




TECHNICAL SPECIFICATIONS | TRACK-MOUNTED SCREENING PLANT

# MOBISCREEN MS 23 D





## TECHNICAL HIGHLIGHTS

- Triple-deck screening unit
- Diesel-electric drive
- Classifying screen for four final products
- Max. feed size: 8"

## TECHNICAL SPECIFICATIONS MS 23 D - US SPEC

### Feeding unit

Feed capacity up to approx. (US t/h)	882
Feed size max. (inch)	8"
Feed height (inch)	11' 2"

### Belt conveyor feeder

Width x length (inch)	6' x 46'
-----------------------	----------

### Screening unit

Type	triple-deck vibration screen
Width x length (inch)	7' 7" x 26' 3"

### Bottom deck underflow discharge conveyor (fine fractions)

Width x length (inch)	6' x 46'
Discharge height approx. (inch)	19' 7"

### Belt conveyor screen overflow (bottom deck)

Width x length (inch)	2' 8" x 12' 6"
-----------------------	----------------

### Bottom deck overflow discharge conveyor (medium fractions 1)

Width x length (inch)	2' 8" x 32' 10"
Discharge height approx. (inch)	14' 5"

### Belt conveyor screen overflow (middle deck)

Width x length (inch)	2' 8" x 12' 6"
-----------------------	----------------

### Middle deck overflow

#### discharge conveyor (medium fractions 2)

Width x length (inch)	2' 8" x 32' 10"
Discharge height approx. (inch)	14' 5"

### Belt conveyor oversize grain

Width x length (inch)	3' 4" x 12' 6"
-----------------------	----------------

### Top deck overflow

#### discharge conveyor (oversize fractions)

Width x length (inch)	3' 4" x 32' 10"
Discharge height approx. (inch)	14' 5"

### Drive

Drive concept	diesel-electric
Powerpack Scania (Tier 4f/Stage IV) (hp)	303
Generator (kVA)	250

### Weight

Operating weight approx. (lbs)	125,600
Machine dismantled for transport	