HAMM

Technical data

HC 268i VC



Compactors Series HC
Compactor with vibration crusher drum

H260

HIGHLIGHTS

> 3-point articulation for good traction and off-road capability
> 2 in 1: Crushing and compacting in one process
> High crushing force owing to high point load
> Wide range of applications (e.g. road construction, landfill site construction, surface mining, etc.)
> New toolholder system for simple tool changes

TECHNICAL DATA HC 268i VC (H260)

Weights		
Operating weight with cab	kg	25690
Max. operating weight	kg	26470
Axle load, front/rear	kg	17420/8270
Axle load at max. operating weight, front/rear	kg	18400/8070
Static linear load, front	kg/cm	82,64
French classification, value/class		-
Wheel load per tyre, rear	kg	4135
Machine dimensions		
Total length	mm	6955
Total height	mm	3061
Height loading, min.	mm	3061
Centre distance	mm	3615
Total width	mm	2496
Maximum working width	mm	2140
Ground clearance, centre	mm	441
Kerb clearance, left/right	mm	580/580
Turning radius, inside	mm	4904
Slope angle, front/rear	°	44,6/28,5
Drum dimensions		
Drum width, front	mm	2140
Drum diameter, front	mm	1710
Drum thickness, front	mm	35
Drum type, front		VC
Tool holder, quantity		126
Tyre dimensions		
Tyre size, rear		EM 23.5-R25 PR
Width over tyres, rear	mm	2235
Number of tyres, rear		2
Diesel engine		
Manufacturer		CUMMINS
Model		B5.9CS4 210C
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		154/209/2200
Power SAE J1349, kW/HP/rpm		154/206/2200
Exhaust emissions category, China		MEE 4
Exhaust gas after-treatment		DOC-DPF
Travel drive		
Speed, infinitely variable	km/h	0 - 8,0
Regulation, infinitely variable		HAMMTRONIC/manual
Gradeability, with/without vibration	%	56/61
Vibration		
Vibration frequency, front	Hz	27
Amplitude, front	mm	2,05
Centrifugal force, front	kN	350,0
Steering		
Steering angle +/-	°	32
Pendulum angle +/-	°	10

Steering		
Steering, type		Articulated steering
Tank capacity/filling capacity		
Fuel tank, capacity	L	321
Sound level		
Sound power level L(WA), guaranteed	db(A)	
Sound power level L(WA), representative measurement	db(A)	107

EQUIPMENT

Dashboard with displays, indicator lights and switches | Driver's platform with access on one side | Vibration-isolated driver's platform | Seat length adjustment | 1 drive lever | ECO mode | Hydrostatic steering | 3-point articulation | Battery isolation switch | Hose protection on the front vehicle | Vibration crusher drum | VC tool-changing system | Transport rings for vibration crusher drum | Plastic protective roof, reinforced with fibre glass and folding

OPTIONAL EQUIPMENT

Cab with air-conditioning system, without heating | HAMM Compaction Meter (HCM) | Back-up alarm | Working spotlights | Rotating beacon | Tool kit

Further data on request/subject to change Illustrations may contain optional features.© **Hamm AG** 2026 - WX3407859 en-GB V2