HAMM

Technical data

HC 200 G P



Compactors Series HC | **H345**

Compactor with smooth drum

HIGHLIGHTS

> High compaction performance
> Ergonomic driver platform
> Simple, intuitive and language-neutral control
> 3-point articulation for good traction and off-road capability
> Good visibility of machine and jobsite
> Electronic machine management Hammtronic
> Easy maintenance and servicing

G

TECHNICAL DATA HC 200 G P (H345)

Weights		
Operating weight with cab	kg lbs	20720 45,688
Max. operating weight	kg lbs	20820 45,908
Axle load, front/rear	kg lbs	13050/7670 28,775/16,912
Axle load at max. operating weight, front/rear	kg lbs	13100/7720 28,885/17,023
Static linear load, front	kg/cm lbs/in	61,0 341.6
French classification, value/class		83,0/VPM5
Wheel load per tire, rear	kg lbs	3835 8,456
Machine dimensions		
Total length	mm in	6847 269.6
Total height	mm in	3301 130.0
Height loading, min.	mm in	2803 110.4
Center distance	mm in	3433 135.2
Total width	mm in	2350 92.5
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	441 17.4
Curb clearance, left/right	mm in	505/505 19.9/19.9
Turning radius, inside	mm in	5159 203.1
Slope angle, front/rear	°	35/29
Drum dimensions		
Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1680 66.1
Drum thickness, front	mm in	30 1.2
Drum type, front		Padfoot
Height of the padfeet	mm in	100 3.9
Padfeet, quantity		130
Tire dimensions		
Tire size, rear		AW 23.1-26 12 PR
Width over tires, rear	mm in	2235 88.0
Diesel engine		
Manufacturer		CUMMINS
Model		QSB5.9-C210-30
Cylinders, quantity		6

Diesel engine		
Power ISO 14396, kW/PS/rpm		154/209/2200
Power SAE J1349, kW/HP/rpm		154/206/2200
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust emissions category, Brazil		MAR 1
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h mph	0-12,2 0.0-7.6
Gradeability, with/without vibration	%	55/61
Vibration		
Vibration frequency, front, level I/II	Hz vpm	27/30 1,620/1,800
Amplitude, front, level I/II	mm in	1,85/1,10 .073/.043
Centrifugal force, front, level I/II	kN lbs	331/242 74,475/54,450
Steering		
Steering angle +/-	°	32
Pendulum angle +/-	°	10
Steering, type		Articulated steering
Tank capacity/filling capacity		
Fuel tank, capacity	L Gal	321 84.8
Sound level		
Sound power level L(WA), guaranteed	db(A)	
Sound power level L(WA), representative measurement	db(A)	107

EQUIPMENT

OPTIONAL EQUIPMENT

WIRTGEN AMERICA • 6030 Dana Way • Antioch, TN 37013 • Phone +1 615-501-0600 • Fax +1 615-501-0691 • info.america@wirtgen-group.com • www.wirtgen-group.com/america

HAMM AG • Hammstr. 1 • D-95643 Tirschenreuth • Tel +49 9631 80-0 • Fax +49 9631 80-111 • www.hamm.eu

Further data on request/subject to change Illustrations may contain optional features.© **Hamm AG** 2026 - WX3372361 en-US V1

HAMM