

Technical information

MOBISCREEN MSS 1102 PRO



Track-mounted screening plant

Use in natural stone and recycling

MOBISCREEN MSS PRO

Series

HIGHLIGHTS

- > Double-deck screening unit
- > Scalping screen
- > Diesel-hydraulic drive
- > Max. feed size: 800 x 500 x 300 mm

TECHNICAL DATA MSS 1102 PRO

Feeding unit

Feed capacity up to approx. (t/h)	500
Feed size max. (mm)	800 x 500 x 300
Feed height (mm)	3,760
Hopper capacity (m ³)	11.5

Feeding conveyor

Width x length (mm)	1,500 x 4,800
Type (optional)	variable speed

Screening unit

Type	double-deck screen
Top deck width x length (mm)	1,830 x 6,100
Bottom deck width x length (mm)	1,830 x 5,490

Belt conveyor underflow material

Width x length (mm)	1,400 x 5,520
---------------------	---------------

Discharge conveyor underflow lower deck (fine grain)

Width x length (mm)	1,050 x 7,910
Discharge height approx. (mm)	3,940

Bottom deck overflow discharge conveyor (medium fractions)

Width x length (mm)	900 x 8,080
Discharge height approx. (mm)	3,570

Top deck overflow discharge conveyor (oversize fractions)

Width x length (mm)	1,600 x 5,840
Discharge height approx. (mm)	3,800

Drive

Drive concept	diesel-hydraulic
Powerpack CAT (Tier 3, 4f) (kW)	168
Powerpack CAT (Stage V) (kW)	168

Transport

Transport height approx. (mm)	3,490
Transport length approx. (mm)	16,965
Transport width approx. (mm)	3,020
Transport weight approx. (kg)	37,500

OPERATING POSITION

