

Technical data

3518 P



Compactors Series 3000

Compactor with padfoot drum

H176

HIGHLIGHTS

- > 3-point articulation for excellent traction and cross-country mobility
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tiltable steering column
- > Simple, intuitive and language-neutral control
- > High compaction performance due to linear load and big amplitudes
- > Excellent view of machine and construction site

TECHNICAL DATA 3518 P (H176)

Weights

Operating weight with cab	kg lbs	18025 39,745
Operating weight with ROPS	kg lbs	17805 39,260
Operating weight, max.	kg lbs	19760 43,571
Axle load, front/rear	kg lbs	10985/7040 24,222/15,523
French classific., data/class		68,77/VPM4

Machine dimensions

Total length	mm in	6210 244.5
Total height with cab	mm in	3050 120.1
Height, loading, min.	mm in	2350 92.5
Wheelbase	mm in	3165 124.6
Total width with cab	mm in	2390 94.1
Ground clearance, center	mm in	425 16.7
Turning radius, inside	mm in	4180 164.6
Angle of driving slope, front/rear	°	37/27

Drum dimensions

Drum width, front	mm in	2220 87.4
Drum diameter, front	mm in	1784 70.2
Drum thickness, front	mm in	35 1.4
Drum type, front		Padfoot
Height of padfeet	mm in	100 3.9
Padfeet, number		150

Wheel dimensions

Size of tires, rear		TR 23.1-26 12 PR
---------------------	--	------------------

Diesel engine

Manufacturer		DEUTZ
Type		TCD 2012 L06 2V
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm		155,0/207,7/2300
Emission standard		EU Stage IIIA/EPA Tier 3

Drive

Speed, working gear	km/h mph	0-3,8/0-5,3/0-5,9 0.0-2.4/0.0-3.3/0.0-3.7
---------------------	-------------	--

Drive

Speed, transportation gear	km/h mph	0-11,1 0.0-6.9
Climbing ability, vibration on/off	%	55/60

Vibration

Vibration frequency, front, I/II	Hz vpm	27/30 1,620/1,800
Amplitude, front, I/II	mm in	1,93/1,15 .076/.045
Centrifugal force, front, I/II	kN lbs	331/243 74,475/54,675

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L Gal	290 76.6
---------------------	----------	-------------

Sound level

Sound power level L(WA), guaranteed	db(A)	105
Acoustic power L(WA), measured	db(A)	103

EQUIPMENT

2 armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Control platform with steering column adjustment | Operator's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated operator's platform | Stepless hydrostatic all-wheel drive | Handrail at operator's platform | Dozer blade

OPTIONAL EQUIPMENT

ROPS, rigid | Auxiliary heater | Radio | Protective roof | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Speedometer | Frequency display, vibration | Back-up alarm | Automatic vibration system | Working light | Rotating beacon | Protective grille for lighting package | Hose protection