



**Tandem rollers Series HD** 

andem roller with vibrating roller drum and set of wheels

H181

## **HIGHLIGHTS**

- > Excellent view of the machine and the construction site
- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Simple, intuitive and language-neutral operation
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat

HD 110K | TECHNICAL DATA

## **TECHNICAL DATA HD 110K (H181)**

Weights		
Operating weight with cab	kg	9230
Operating weight with ROPS	kg	8965
Maximum operating weight	kg	11890
Static linear load, front	kg/cm	31,5
French classification, value/class		28,9.9,8/VX2.PLO
Machine dimensions		
Total length	mm	4600
Total height with cab	mm	3060
Height loading, min.	mm	2360
Centre distance	mm	3400
Total width with cab	mm	1810
Maximum working width	mm	1750
Kerb clearance, left/right	mm	790/790
Turning radius, inside	mm	4500
Drum dimensions		
Drum width, front	mm	1680
Drum diameter, front	mm	1200
Drum thickness, front	mm	22
Drum type, front		Smooth/non-split
Track offset, left/right	mm	100
Tyre dimensions		
Tyre size, rear		11.00-20
Width over tyres, rear	mm	1620
Number of tyres, rear		4
Diesel engine		
Manufacturer		DEUTZ
Model		TCD 2012 L04 2V
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power SAE J1349, kW/HP/rpm		100,0/134,0/2300
Exhaust emission standard		EU Stage IIIA / EPA Tier 3
Travel drive		
Speed, working gear	km/h	0-7,4
Speed, transport gear	km/h	0-14,8
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, I/II	Hz	42/50
Amplitude, front, I/II	mm	0,84/0,49
Centrifugal force, front, I/II	kN	120/99
Steering		
Pendulum angle +/-	٥	10
Steering, type		Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capacity		
Fuel tank, capacity	L	185
, ,		
Water tank, capacity	L	700
Water tank, capacity  Additive tank, capacity	L	700

Sound level		
Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	107

## **EQUIPMENT**

2 drive levers | Switchable amplitude: Big/small | Left/right handrails | Lighting package for driving on public roads | Driver's platform with access from both sides | Seat operating unit, rotatable | Seat operating unit, rotatable, with armrests and seat belt | Vibration front and rear, single and double, switchable

## **OPTIONAL EQUIPMENT**

Air-conditioning system | Tachograph | Fire extinguisher | Protective roof | Edge pressing and cutting equipment | Frequency control | HCQ compaction meter | Speedometer | Back-up alarm | Telematics system | Automatic vibration system | Working spotlights | Rotating beacon | Locking device | Tool kit

