

Technical data

HD 14 VV



Tandem rollers Series HD CompactLine

Γandem roller with two vibration drums

H201

HIGHLIGHTS

- > Compact dimensions
- > Easy transport, simple loading
- > Simple, intuitive and language-neutral operation
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Ergonomic driver platform

TECHNICAL DATA HD 14 VV (H201)

Weights		
Operating weight with ROPS	kg	4345
Max. operating weight	kg	5300
Static linear load, front/rear	kg/cm	15,8/15,7
French classification, value/class		10,2/VT0
Machine dimensions		
Total length	mm	2896
Total height with cab	mm	2720
Total height with ROPS	mm	2590
Height loading, min.	mm	1820
Centre distance	mm	1950
Total width	mm	1506
Maximum working width	mm	1430
Kerb clearance, left/right	mm	720/720
Turning radius, inside	mm	2650
Drum dimensions		
Drum width, front/rear	mm	1380/1380
Drum diameter, front/rear	mm	898/898
Drum thickness, front/rear	mm	16/16
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50
Diesel engine		
Manufacturer		KUBOTA
Model		V2203
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		34,6/47,1/2700
Power SAE J1349, kW/HP/rpm		34,6/46,4/2700
Exhaust emission standard		EU Stage 3A
Exhaust gas after-treatment		-
Travel drive		
Speed, infinitely variable	km/h	0 - 11,0
Gradeability, with/without vibration	%	30/40
Vibration		
Vibration frequency, front, level I/II	Hz	57/48
Vibration frequency, rear, level I/II	Hz	57/48
Amplitude, front, level I/II	mm	0,51/0,31
Amplitude, rear, level I/II	mm	0,51/0,31
Centrifugal force, front, level I/II	kN	58/35
Centrifugal force, rear, level I/II	kN	58/35
Steering		
Pendulum angle +/-	٥	8
Steering, type		Articulated steering
Water-sprinkling system		
Water sprinkling, type		Pressure
Tank capacity/filling capaci	ty	
Fuel tank, capacity	L	73

Tank capacity/filling capacity			
Water tank, capacity	L	260	
Sound level			
Sound power level L(WA), guaranteed	db(A)	106	
Sound power level L(WA), representative measurement	db(A)	103	

EQUIPMENT

3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Left/right handrails | Pressure water sprinkling system | Driver's platform with access from both sides | Hydrostatic steering | Vibration-isolated driver's platform | Track offset

OPTIONAL EQUIPMENT

Plastic scraper, folding | ROPS, foldable | Edge pressing and cutting device | Chip spreader | Anti-freeze injection system | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Drum edge lighting | Water drain valve | Towing eye, front | Tow hitch | V-belt protection

