

Technical data

# HD 75K



## Tandem rollers Series HD

Tandem roller with vibrating roller drum and set of wheels

H187

### HIGHLIGHTS

- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Excellent view of the machine and the construction site
- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Simple, intuitive and language-neutral operation
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat

## TECHNICAL DATA HD 75K (H187)

## Weights

Operating weight with cab	kg	7335
Operating weight with ROPS	kg	7070
Maximum operating weight	kg	9790
Static linear load, front	kg/cm	23,1
French classification, value/class		17,4.8,6/VX1.PLO

## Machine dimensions

Total length	mm	4340
Total height with cab	mm	2940
Height loading, min.	mm	2260
Centre distance	mm	3200
Total width with cab	mm	1790
Maximum working width	mm	1750
Kerb clearance, left/right	mm	780/780
Turning radius, inside	mm	4084

## Drum dimensions

Drum width, front	mm	1680
Drum diameter, front	mm	1140
Drum thickness, front	mm	17
Drum type, front		Smooth/non-split
Track offset, left/right	mm	100

## Tyre dimensions

Tyre size, rear		11.00-20
Width over tyres, rear	mm	1620
Number of tyres, rear		4

## Diesel engine

Manufacturer		DEUTZ
Model		TD 2011 L04 W
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2500
Power SAE J1349, kW/HP/rpm		55,4/74,2/2500
Exhaust emission standard		EU Stage IIIA / EPA Tier 3

## Travel drive

Speed, working gear	km/h	0-6,3
Speed, transport gear	km/h	0-12,6
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, I/II	Hz	48/58
Amplitude, front, I/II	mm	0,61/0,33
Centrifugal force, front, I/II	kN	77/63

## Steering

Pendulum angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	140
Water tank, capacity	L	580
Additive tank, capacity	L	11

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

## EQUIPMENT

2 drive levers | Switchable amplitude: Big/small | Left/right handrails | Lighting package for driving on public roads | Driver's platform with access from both sides | Speedometer | Seat operating unit, rotatable | Seat operating unit, rotatable, with armrests and seat belt | Vibration front and rear, single and double, switchable

## OPTIONAL EQUIPMENT

Heating and air-conditioning system | Protective roof | Edge pressing and cutting equipment | Engine rpm counter | HAMM Temperature Meter (HTM) | Track offset display | Back-up alarm | Working spotlights | Rotating beacon | Water tank cover, lockable