

Technical data

3411 P



Compactors Series 3000

Compactor with padfoot drum

H179

HIGHLIGHTS

- > 3-point articulation for excellent traction and cross-country mobility
- > High compaction performance due to linear load and big amplitudes
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tiltable steering column
- > Excellent view of machine and construction site
- > Simple, intuitive and language-neutral control

TECHNICAL DATA 3411 P (H179)

Weights		
Operating weight with cab	kg lbs	11800 26,019
Operating weight with ROPS	kg lbs	11580 25,534
Operating weight, max.	kg lbs	13330 29,393
Axle load, front/rear	kg lbs	6615/5185 14,586/11,433
French classific., data/class		47,8/VPM3
Machine dimensions		
Total length	mm in	5695 224.2
Total height with cab	mm in	3040 119.7
Height, loading, min.	mm in	2320 91.3
Wheelbase	mm in	3005 118.3
Total width with cab	mm in	2250 88.6
Ground clearance, center	mm in	375 14.8
Turning radius, inside	mm in	4005 157.7
Angle of driving slope, front/rear	°	34/34
Drum dimensions		
Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1684 66.3
Drum thickness, front	mm in	15 0.6
Drum type, front		Padfoot
Height of padfeet	mm in	100 3.9
Padfeet, number		140
Wheel dimensions		
Size of tires, rear		TR 23.1-26 12 PR
Diesel engine		
Manufacturer		DEUTZ
Type		TCD 2012 L04 2V
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300
Emission standard		EU Stage IIIA/EPA Tier 3
Drive		
Speed, working gear	km/h mph	0-5,8/0-7,2/0-8,4 0.0-3.6/0.0-4.5/0.0-5.2

Drive		
Speed, transportation gear	km/h mph	0-11,7 0.0-7.3
Climbing ability, vibration on/off	%	51/56
Vibration		
Vibration frequency, front, I/II	Hz vpm	27/37 1,620/2,220
Amplitude, front, I/II	mm in	1,90/0,80 .075/.031
Centrifugal force, front, I/II	kN lbs	246/144 55,350/32,400
Steering		
Oscillation angle +/-	°	10
Steering, type		Articulated steering
Tank capacity/Fill capacity		
Fuel tank, capacity	L Gal	290 76.6
Sound level		
Sound power level L(WA), guaranteed	db(A)	107
Acoustic power L(WA), measured	db(A)	103

EQUIPMENT

2 armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Control platform with steering column adjustment | Operator's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated operator's platform | Stepless hydrostatic all-wheel drive | Handrail at operator's platform | Dozer blade | Sound insulation

OPTIONAL EQUIPMENT

ROPS cabin | ROPS, rigid | Auxiliary heater | Radio | Protective roof | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Speedometer | Frequency display, vibration | Back-up alarm | Telematics interface | Automatic vibration system | Working light | Rotating beacon | Lamp protection | Hydraulic hose protection on front frame