

Technical data

3412 HT P



Compactors Series 3000

Compactor with padfoot drum

H180

HIGHLIGHTS

- > Simple, intuitive and language-neutral control
- > Electronic machine management Hammtronic
- > 3-point articulation for excellent traction and cross-country mobility
- > Ergonomic driver platform with rotatable seat operating unit, adjustable driver's seat and tiltable steering column
- > Excellent view of machine and construction site

TECHNICAL DATA 3412 HT P (H180)

Weights

Operating weight with cab	kg lbs	12300 27,121
Operating weight with ROPS	kg lbs	12080 26,636
Basic weight no cab, without ROPS	kg lbs	11630 25,644
Operating weight, max.	kg lbs	13830 30,495
Axle load, front/rear	kg lbs	6805/5495 15,005/12,116
French classific., data/class		43,4/VPM3
Load per tire, rear	kg lbs	2747,5 6,058

Machine dimensions

Total length	mm in	5705 224.6
Total height with cab	mm in	3010 118.5
Total height with ROPS	mm in	2945 115.9
Height, loading, min.	mm in	2325 91.5
Wheelbase	mm in	3015 118.7
Total width with cab	mm in	2250 88.6
Max. working width	mm in	2140 84.3
Ground clearance, center	mm in	375 14.8
Curb clearance, left/right	mm in	465/465 18.3/18.3
Turning radius, inside	mm in	3690 145.3
Angle of driving slope, front/rear	°	35/34

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1684 66.3
Drum thickness, front	mm in	20 0.8
Drum type, front		Padfoot
Height of padfeet	mm in	100 3.9
Padfeet, number		140

Wheel dimensions

Size of tires, rear		TR 23.1-26 12 PR
Width over tires, rear	mm in	2130 83.9
Number of tires, rear		2

Diesel engine

Type		TCD 2012 L04 2V
Number of cylinders		4
Power rat. ISO 14396, kW/PS/rpm		100,0/136,0/2300
Power rating SAE J1349, kW/HP/rpm		100,0/134,0/2300
Emission standard		EU Stage IIIA/EPA Tier 3

Drive

Speed, infinitely variable	km/h mph	0 - 14,0 0.0 - 8.7
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	65/70

Vibration

Vibration frequency, front, I/II	Hz vpm	30/40 1,800/2,400
Amplitude, front, I/II	mm in	1,90/0,90 .075/.035
Centrifugal force, front, I/II	kN lbs	256/215 57,600/48,375

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L Gal	290 76.6
---------------------	----------	-------------

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power L(WA), measured	db(A)	103

EQUIPMENT

2 armrests | 3-point articulation | Adjustable scraper | Dashboard with displays, indicator lights and switches | Automatic traction control and anti-slip control | Battery isolation switch | Control platform with steering column adjustment | Operator's platform with entry from both sides | Speed preselect | Hydrostatic steering | Vibration-isolated operator's platform | Stepless hydrostatic all-wheel drive

OPTIONAL EQUIPMENT

Auxiliary heater | Radio | Tachograph | HCQ navigator | Protective roof | Version with additional fuel prefilter | HAMM Compaction Meter (HCM) | Frequency display, vibration | Back-up alarm | Telematics interface | Working light | Rotating beacon | Protective grille for lighting package | Hydraulic hose protection on front frame | Tool kit