



Technical data

H 20i C P



Soil Compactors Series H

Soil compactor with padfoot drum

H268

HIGHLIGHTS

- > High compaction performance thanks to high line load and big amplitudes
- > Operating concept Easy Drive
- > Electronic machine management Hammtronic
- > Excellent view of the machine and the construction site
- > 3-point articulation for outstanding traction and off-road mobility

TECHNICAL DATA H 20i C P (H268)

Weights

Operating weight with cab	kg	20905
Operating weight with ROPS	kg	20715
Operating weight, max.	kg	20930
Axle load, front/rear	kg	13800/7105
French classific., data/class		89,6/VPM5
Load per tyre, rear	kg	3552,5

Machine dimensions

Total length	mm	6600
Total height with cab	mm	2970
Height loading, min.	mm	2320
Wheel base	mm	3265
Total width with cab	mm	2308
Ground clearance, centre	mm	390
Turning radius, inside	mm	4200
Angle of driving slope, front/rear	°	43/28

Drum dimensions

Drum width, front	mm	2140
Drum diameter, front	mm	1784
Drum thickness, front	mm	35
Drum type, front		Padfoot
Height of the padfeet	mm	100
Padfeet, number		150

Wheel dimensions

Size of tyres, rear		TR 23.1-26 12 PR
Width over tyres, rear	mm	2160
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Version		TCD 6.1 L6
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		160,0/217,6/2300
Power rating SAE J1349, kW/HP/rpm		160,0/214,4/2300
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Drive

Speed, infinitely variable	km/h	0 - 10,0
Regulation, infinitely variable		Hammtronic
Climbing ability, vibration on/off	%	61/66

Vibration

Vibration frequency, front, I/II	Hz	27/30
Amplitude, front, I/II	mm	1,93/1,14
Centrifugal force, front, I/II	kN	331/242

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L	280
---------------------	---	-----

Tank capacity/Fill capacity

AdBlue/DEF tank, content	L	32
--------------------------	---	----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power L(WA), measured	db(A)	104

EQUIPMENT

12 V sockets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Automatic vibration system | Lighting package as per road traffic regulations | Camera system

OPTIONAL EQUIPMENT

ROPS cabin with heating and air conditioning, FOPS-approved (level I) | Safety belt monitoring device | Armrest comfort setting, left | Auxiliary heater | Radio | Tachograph | Bluetooth interface for Smart Doc | HCQ Navigator | Dozer blade | Frequency regulation | HAMM Compaction Meter (HCM) | Automatic engine-off function | Telematics interface | Working lights | Rotating beacon | Bonnet with electrical easy access engine cover release | Coming home lighting | Battery isolating switch | Homologation | Tool kit