

Technical data

H 25i VC



Soil Compactors Series H

Soil compactor with vibration crusher drum

H268

HIGHLIGHTS

- > 2 in 1: Crushing and compacting in one process
- > High crushing force owing to high point load
- > High flexibility – use for standard and special applications
- > Simple tool changing thanks to patented holder exchange system
- > 3-point articulation for outstanding traction and off-road mobility

TECHNICAL DATA H 25i VC (H268)

Weights

Operating weight with cab	kg	25260
Basic weight no cab, without ROPS	kg	24510
Operating weight, max.	kg	25650
Axle load, front/rear	kg	16770/8490
French classific., data/class		109,2/VPM5
Load per tyre, rear	kg	4245

Machine dimensions

Total length	mm	6751
Total height with cab	mm	2970
Height loading, min.	mm	2320
Wheel base	mm	3261
Total width with cab	mm	2540
Ground clearance, centre	mm	400
Turning radius, inside	mm	4760
Angle of driving slope, front/rear	°	40/28

Drum dimensions

Drum width, front	mm	2220
Drum diameter, front	mm	1710
Drum thickness, front	mm	35
Drum type, front		VC
Tool holder, quantity		150

Wheel dimensions

Size of tyres, rear		EM 23.5-R25 XTLA
Width over tyres, rear	mm	2160
Number of tyres, rear		2

Diesel engine

Manufacturer		DEUTZ
Version		TCD 6.1 L6
Number of cylinders		6
Power rat. ISO 14396, kW/PS/rpm		160,0/217,6/2300
Power rating SAE J1349, kW/HP/rpm		160,0/214,4/2300
Emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Drive

Speed, infinitely variable	km/h	0 - 8,0
Regulation, infinitely variable		Hammtronic/manual
Climbing ability, vibration on/off	%	61/66

Vibration

Vibration frequency, front	Hz	27
Amplitude, front	mm	2,09
Centrifugal force, front	kN	351

Steering

Oscillation angle +/-	°	10
Steering, type		Articulated steering

Tank capacity/Fill capacity

Fuel tank, capacity	L	280
---------------------	---	-----

Tank capacity/Fill capacity

AdBlue/DEF tank, content	L	32
--------------------------	---	----

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Acoustic power L(WA), measured	db(A)	104

EQUIPMENT

12 V sockets (double) | 2 large working and rear view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function key | Operating concept Easy Drive | ECO mode | Speed preselect | Hose protection on front vehicle | Automatic vibration system | Lighting package as per road traffic regulations | Insert for tools | Frequency regulation | HAMM Compaction Meter (HCM) | Camera system | Working lights

OPTIONAL EQUIPMENT

ROPS cabin with heating and air conditioning, FOPS-approved (level I) | Safety belt monitoring device | Auxiliary heater | Radio | Tachograph | Bluetooth interface for Smart Doc | HCQ Navigator | Automatic engine-off function | Telematics interface | Rotating beacon | Bonnet with electrical easy access engine cover release | Coming home lighting | Battery isolating switch | Homologation | Tool kit