

Technical data

# HD+ 80i OT



## Tandem rollers Series HD+

Tandem roller with oscillation drum and set of wheels

H272

### HIGHLIGHTS

- > Excellent view of the machine and the construction site
- > Simple, intuitive and language-neutral operation
- > Compaction with oscillation
- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Seat operating unit can be moved and rotated

## TECHNICAL DATA HD+ 80i OT (H272)

## Weights

Operating weight with cab	kg	7460
Operating weight with ROPS	kg	7290
Max. operating weight	kg	9920
Static linear load, front	kg/cm	27,65
French classification, value/class		-8,6/-P.LO

## Machine dimensions

Total length	mm	4480
Total height with cab	mm	2890
Total height with ROPS	mm	2970
Height loading, min.	mm	2080
Centre distance	mm	3340
Total width with cab	mm	1800
Maximum working width	mm	1780
Ground clearance, centre	mm	340
Kerb clearance, left/right	mm	750/750
Turning radius, inside	mm	4140

## Drum dimensions

Drum width, front	mm	1680
Drum diameter, front	mm	1140
Drum thickness, front	mm	20
Drum type, front		Smooth/non-split
Track offset, left/right	mm	135

## Tyre dimensions

Tyre size, rear		11.00-20
Width over tyres, rear	mm	1614
Number of tyres, rear		4

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 2.9 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2300
Power SAE J1349, kW/HP/rpm		55,4/74,2/2300
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

## Travel drive

Speed, infinitely variable	km/h	0 - 9,9
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	36/46

## Oscillation

Oscillation force, front	kN	105,11
Oscillation frequency, front	Hz	40
Tangential amplitude, front	mm	0,93

## Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Water tank, capacity	L	700
Additive tank, capacity	L	18

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

## EQUIPMENT

12 V power socket | Two large exterior rear-view mirrors | Folding scraper | Dashboard with displays, indicator lights and switches | Tilttable dashboard | Pressure water sprinkling system | ECO mode | Driver's platform with entry from both sides | Speed-controlled water sprinkling | Speed preselect | Automatic traction control and anti-slip control | Vibration-insulated driver's platform | Track offset, hydraulic | Water-sprinkling system with spray bars front and rear | Water filter system (3-fold) | Water tank front and rear, can be filled from both sides | Central water outlet

## OPTIONAL EQUIPMENT

Heating | Heating and air conditioning | Steering column with comfort exit and tilttable dashboard | Additional drive lever, left | Tachograph | Protective roof | Edge pressing and cutting equipment | HAMM Temperature Meter (HTM) | Track offset display | Working lights | Rotating beacon