



Tandem rollers Series HD CompactLine

andem roller with two sets of wheels

H208

HIGHLIGHTS

- > Simple, intuitive and language-neutral control
- > Simple transport, simple loading
- > Ergonomic driver platform
- > Excellent view of tires, machine and construction site
- > Compact dimensions

HD 14 TT | **TECHNICAL DATA**

TECHNICAL DATA HD 14 TT (H208)

| Weights | | |
|------------------------------------|-------------|---------------------------|
| Operating weight with ROPS | kg lbs | 3470 7,651 |
| Max. operating weight | kg lbs | 4320 9,526 |
| French classification, value/class | | 5,4/PLO |
| Wheel load per tire, front/rear | kg lbs | 535/466,25 1,180/1,028 |
| Machine dimensions | | |
| Total length | mm in | 2896 114.0 |
| Total height with ROPS | mm in | 2590 102.0 |
| Height loading, min. | mm in | 1820 71.7 |
| Center distance | mm in | 1950 76.8 |
| Total width | mm in | 1296 51.0 |
| Maximum working width | mm in | 1276 50.2 |
| Ground clearance, center | mm in | 305 12.0 |
| Turning radius, inside | mm in | 2602 102.4 |
| Tire dimensions | | |
| Size of tires, front/rear | | 10.5/80-16 |
| Width over tires, front/rear | mm in | 1127/1276 44.4/50.2 |
| Number of tires, front/rear | | 3/4 |
| Diesel engine | | |
| Manufacturer | | Kubota |
| Model | | V2203 |
| Cylinders, quantity | | 4 |
| Power ISO 14396, kW/PS/rpm | | 34,6/47,1/2700 |
| Power SAE J1349, kW/HP/rpm | | 34,6/46,4/2700 |
| Exhaust emission standard | | EU Stage IIIA |
| Exhaust gas after-treatment | | - |
| Travel drive | | |
| Speed, infinitely variable | km/h mph | 0-10,0 0.0-6.2 |
| Gradeability | % | 40 |
| Steering | | |
| Steering, type | | Articulated steering |
| Water-sprinkling system | | |
| Water sprinkling, type | | Pressure |
| Tank capacity/filling capacit | у | |
| Fuel tank, capacity | L Gal | 73 19.3 |

| Tank capacity/filling capacity | | | |
|---|----------|-------------|--|
| Water tank, capacity | L Gal | 260 68.7 | |
| Sound level | | | |
| Sound power level L(WA), guaranteed | db(A) | 101 | |
| Sound power level L(WA), representative measurement | db(A) | 100 | |

EQUIPMENT

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Left/right handrails | Battery isolation switch | Pressure water sprinkling system | Driver's platform with entry from both sides | Hydrostatic steering | Vibration-isolated driver's platform | CompactLine front towing eye

OPTIONAL EQUIPMENT

Additive sprinkling | Automatic engine stop | Back-up alarm | Working spotlights | Rotating beacon | Water drain valve | Tow hitch | V-belt protection

WIRTGEN AMERICA • 6030 Dana Way • Antioch, TN 37013 • Phone +1 615-501-0600 • Fax +1 615-501-0691 • info.america@wirtgen-group.com • www.wirtgen-group.com/america

