

Technical data

# HD+ 80i VT



## Tandem rollers Series HD+

Tandem roller with vibrating roller drum and set of wheels

H186

### HIGHLIGHTS

- > 3-point articulation for even weight distribution and excellent directional stability
- > Track offset for comfortable starting and driving away and compacting at curbsides
- > Simple, intuitive and language-neutral control
- > Excellent view of machine and construction site
- > Seat-operating unit can be moved and rotated

## TECHNICAL DATA HD+ 80i VT (H186)

## Weights

Operating weight with cab	kg lbs	7380 16,273
Operating weight with ROPS	kg lbs	7210 15,898
Max. operating weight	kg lbs	9840 21,697
Static linear load, front	kg/cm lbs/in	23,4 131.0
French classification, value/class		18,3.8,6/VX1.PLO

## Machine dimensions

Total length	mm in	4480 176.4
Total height with cab	mm in	2890 113.8
Total height with ROPS	mm in	2970 116.9
Height loading, min.	mm in	2080 81.9
Center distance	mm in	3340 131.5
Total width with cab	mm in	1800 70.9
Maximum working width	mm in	1780 70.1
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	750/750 29.5/29.5
Turning radius, inside	mm in	4140 163.0

## Drum dimensions

Drum width, front	mm in	1680 66.1
Drum diameter, front	mm in	1140 44.9
Drum thickness, front	mm in	17 0.7
Drum type, front		Smooth/non-split
Track offset, left/right	mm in	135 5.3

## Tire dimensions

Tire size, rear		11.00-20
Width over tires, rear	mm in	1614 63.5
Number of tires, rear		4

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 2.9 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2500
Power SAE J1349, kW/HP/rpm		55,4/74,2/2500

## Diesel engine

Exhaust emission standard		EU Stage IIIB / EPA Tier 4
Exhaust gas after-treatment		DOC

## Travel drive

Speed, working gear	km/h mph	0-6,0 0.0-3.7
Speed, transport gear	km/h mph	0-12,0 0.0-7.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, I/II	Hz vpm	48/58 2,880/3,480
Amplitude, front, I/II	mm in	0,61/0,33 .024/.013
Centrifugal force, front, I/II	kN lbs	87/69 19,575/15,525

## Steering

Swing angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L Gal	120 31.7
Water tank, capacity	L Gal	700 184.9
Additive tank, capacity	L Gal	18 4.8

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

## EQUIPMENT

Heating | Steering column with comfort exit and tiltable dashboard | Additional drive lever, left | Protective roof | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | Automatic engine-off function | HAMM Temperature Meter (HTM) | Track offset display | Camera system | Back-up alarm | Telematics interface | Working light | Rotating beacon filter system (3-fold) | Water tank front and rear, can be filled from both sides | Central water outlet

## OPTIONAL EQUIPMENT