

# HD+ 80i VT-S

Tandem roller with vibrating roller drum and set of tires  
Tandem rollers Series HD+ / Series H272




## HIGHLIGHTS HD+












- > 3-point articulation for even weight distribution and excellent directional stability
- > Simple, intuitive and language-neutral control
- > Excellent view of machine and construction site
- > Seat-operating unit can be moved and rotated
- > Track offset for comfortable starting and driving away and compacting at curbsides

## Machine dimensions

Total length (L)	mm • in	4480 • 176.4
Width (B)	mm • in	1800 • 70.9
Total height (H)	mm • in	2890 • 113.8
Drum width (X)	mm • in	1680 • 66.1
Height, loading, min. (HI)	mm • in	2080 • 81.9



EU Stage V /  
EPA Tier 4

TECHNICAL DATA		Unit	HD+ 80i VT-S
	<b>Weights</b>		
Operating weight with cab	kg • lbs		7540 • 16,626
Operating weight with ROPS	kg • lbs		7370 • 16,251
Operating weight, max.	kg • lbs		10000 • 22,050
Static linear load, front	kg/cm • lbs/in		24,3 • 136.1
French classific., data/class			17,5,8,6/XX0.PLO
	<b>Machine dimensions</b>		
Total length	mm • in		4480 • 176.4
Total height with cab	mm • in		2890 • 113.8
Height, loading, min.	mm • in		2080 • 81.9
Wheelbase	mm • in		3340 • 131.5
Total width with cab	mm • in		1800 • 70.9
Max. working width	mm • in		1780 • 70.1
Curb clearance, left/right	mm • in		750/750 • 29.5/29.5
Turning radius, inside	mm • in		4140 • 163.0
	<b>Drum dimensions</b>		
Drum width, front	mm • in		1680 • 66.1
Drum diameter, front	mm • in		1140 • 44.9
Drum thickness, front	mm • in		17 • 0.7
Drum type, front			Smooth/split
Track offset, left/right	mm • in		135 • 5.3
	<b>Wheel dimensions</b>		
Size of tires, rear			11.00-20
Width over tires, rear	mm • in		1614 • 63.5
Number of tires, rear			4
	<b>Diesel engine</b>		
Manufacturer			DEUTZ
Type			TCD 2.9 L4
Power rat. ISO 14396, kW/PS/rpm			55,4/75,3/2300
Power rating SAE J1349, kW/HP/rpm			55,4/74,2/2300
Emission standard			EU Stage V / EPA Tier 4
Exhaust gas after-treatment			DOC-DPF
	<b>Drive</b>		
Speed, infinitely variable	km/h • mph		0 - 10,4 • 0.0 - 6.5
Regulation, infinitely variable			Hammtronic
Climbing ability, vibration on/off	%		40/45
	<b>Vibration</b>		
Vibration frequency, front, I/II	Hz • vpm		42/50 • 2,520/3,000
Amplitude, front, I/II	mm • in		0,52/0,36 • .020/.014
Centrifugal force, front, I/II	kN • lbs		63/63 • 14,175/14,175
	<b>Steering</b>		
Oscillation angle +/-	°		10
Steering, type			Articulated steering
	<b>Sprinkler system</b>		
Water sprinkler, type			Pressure
	<b>Tank capacity/Fill capacity</b>		
Fuel tank, capacity	L • Gal		120 • 31.7
Water tank, capacity	L • Gal		700 • 184.9
Additive tank, capacity	L • Gal		18 • 4.8
	<b>Sound level</b>		
Acoustic power LW(A), sticker	db(A)		106
Acoustic power LW(A), measured	db(A)		105

**EQUIPMENT**  
 12 V outlet, 2 large working and rear view mirrors, Foldable scraper, Dashboard with displays, indicator lights and switches, Tilttable dashboard, Pressure water sprinkling with interval switch, ECO mode, Operator's platform with entry from both sides, Speed-controlled water sprinkling system, Speed preselect, Vibration-insulated operator's platform, Track offset, hydraulic, Spray system with spray bars front and rear, Water filtering (triple), Water tank front and rear, can be filled from both sides, Central water drain

**OPTIONAL EQUIPMENT**  
 Heating, Heating and air conditioning, Steering column with comfort exit and tilttable dashboard, Additional drive lever, left, Tachograph, HCQ navigator, Protective roof, Edge pressing and cutting equipment, HAMM Temperature Meter (HTM), Track offset display, Working light, Rotating beacon

**WIRTGEN AMERICA**  
 6030 Dana Way  
 Antioch, TN 37013  
 Phone +1 615-501-0600  
 Fax +1 615-501-0691  
 info.america@wirtgen-group.com  
 www.wirtgen-group.com/america

**HAMM AG**  
 Hammstraße 1  
 D-95643 Tirschenreuth  
 Tel +49 9631 80-0  
 Fax +49 9631 80-111  
 www.hamm.eu

