

Technical data

HD+ 120i VV-HF



Tandem rollers Series HD+
Tandem roller with two vibration drums

H304

HIGHLIGHTS

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat-operating unit can be moved and rotated
- > Digital ready

TECHNICAL DATA HD+ 120i VV-HF (H304)

Weights

Operating weight with cab	kg lbs	13270 29,260
Operating weight with ROPS	kg lbs	13040 28,753
Empty weight without cab, without ROPS	kg lbs	11955 26,361
Max. operating weight	kg lbs	14290 31,509
Axle load, front/rear	kg lbs	6645/6625 14,652/14,608
Static linear load, front/rear	kg/cm lbs/in	33,56/33,46 187.9/187.4
French classification, value/class		26,98/VT1

Machine dimensions

Total length	mm in	5300 208.7
Total height with cab	mm in	2980 117.3
Total height with ROPS	mm in	3030 119.3
Height loading, min.	mm in	2140 84.3
Center distance	mm in	3900 153.5
Total width with cab	mm in	2145 84.4
Maximum working width	mm in	2150 84.6
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	900/900 35.4/35.4
Turning radius, inside	mm in	6280 247.2

Drum dimensions

Drum width, front/rear	mm in	1980/1980 78.0/78.0
Drum diameter, front/rear	mm in	1400/1400 55.1/55.1
Drum thickness, front/rear	mm in	19/19 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	170 6.7

Diesel engine

Manufacturer		DEUTZ
Model		TCD 4.1 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		115,0/156,4/2300
Power SAE J1349, kW/HP/rpm		115,0/154,1/2300

Diesel engine

Exhaust emissions category, EU		EU Stage 5
Exhaust emissions category, USA		EPA Tier 4
Exhaust emissions category, Japan		JP Stage 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h mph	0-10,5 0.0-6.5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	36/40

Vibration

Vibration frequency, front, level I/II	Hz vpm	45/67 2,700/4,020
Vibration frequency, rear, level I/II	Hz vpm	45/67 2,700/4,020
Amplitude, front, level I/II	mm in	0,70/0,20 .028/.008
Amplitude, rear, level I/II	mm in	0,70/0,20 .028/.008
Centrifugal force, front, level I/II	kN lbs	160/105 36,000/23,625
Centrifugal force, rear, level I/II	kN lbs	160/105 36,000/23,625

Steering

Pendulum angle +/-	°	10
Steering, type		Articulated steering

Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	260 68.7
AdBlue/SCR reducing agent tank, capacity	L Gal	20 5.3
Water tank, capacity	L Gal	1145 302.5

Sound level

Sound power level L(WA), representative measurement	db(A)	109
--	-------	-----

EQUIPMENT

Scraper foldable | Pressure water sprinkling system | ECO mode | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

OPTIONAL EQUIPMENT