

Soil Treatment.

Base Layers with Hydraulic Binders



Contents

1	Soil Treatment	11
1.1	Definition of terms	12
1.1.1	Definitions according to the "Directives for the standardization of the superstructures of trafficked surfaces" (RStO 12)	12
1.1.2	Terms and body of rules and regulations for soil treatment	14
1.1.3	Correlating rules and regulations with the different layers	16
1.2	Definition of terms in soil treatment	18
1.2.1	Soil stabilization	18
1.2.2	Soil improvement	18
1.2.3	Qualified soil improvement	18
1.2.4	Base layers with hydraulic binders	18
1.3	Geotechnical investigations	19
1.3.1	General	19
1.3.2	Description of soil types according to DIN EN ISO 14688-1 (old: 4022, Part 1)	19
1.3.3	Soil classification according to DIN 18196	20
1.3.3.1	Soil groups	20
1.3.3.2	Principles of soil classification	21
1.3.3.3	Coarse-grained soils	22
1.3.3.4	Mixed-grained soils	22
1.3.3.5	Fine-grained soils	22
1.3.3.6	Organogenic and organic soils	22
1.3.3.7	Chart	23
1.3.3.8	Classifying soils according to their plastic properties	24
1.3.3.8.1	Determining consistency	24
1.3.3.8.2	Plasticity chart for classification of fine-grained soils	25
1.3.3.9	Classifying soils according to DIN 18196	26
1.4	Frost susceptibility of soils and rock of variable strength	30
1.4.1	Classifying soil groups in accordance with frost susceptibility	30
1.4.2	Frost susceptibility after soil improvement with binders	31
1.5	Application	32
1.5.1	Soil improvement	32
1.5.2	Qualified soil improvement	32
1.5.2.1	Reducing pavement thickness by means of qualified soil improvement	34

1.5.2.2	Requirements on qualified soil improvement at subgrade level	35
1.5.3	Soil stabilization	36
1.5.3.1	Soil stabilization not counting toward the pavement	36
1.5.3.2	Soil stabilization counting toward the pavement	37
1.5.3.3	Excerpt from the “Directives for the standardization of the superstructures of trafficked surfaces” (RStO 12), Chart 1	38
1.5.3.4	Excerpt from the “Directives for the standardization of the superstructures of trafficked surfaces” (RStO 12), Chart 2	40
1.6	Basic principles of earthworks	42
1.6.1	Compaction	42
1.6.2	Compaction requirements on subsoil and subgrade	42
1.6.3	Requirements on the subgrade	43
1.6.4	Deformation modulus on the subgrade (minimum 10 percentile)	44
1.6.5	Requirements on compaction characteristics	45
1.7	Quality assurance	46
1.7.1	Tests to be performed prior to construction	46
1.7.1.1	Tests to be performed by the client	46
1.7.1.2	Tests to be performed by the contractor	46
1.7.1.3	Testing specifications for mix designs	49
1.7.2	Tests to be performed during construction	50
1.7.2.1	Type and scope of tests to be performed in soil treatment operations	50
1.7.2.2	Testing methods and testing procedures	52
1.7.2.2.1	Testing methods for testing compaction characteristics	53
1.7.2.2.2	Testing procedures for determining compaction parameters	54
1.7.2.2.3	Testing deformation modulus, correct vertical and horizontal position and evenness on the subgrade	57
1.8	Soils and mineral construction materials for soil treatment	58
1.8.1	Suitable soils (according to DIN 18196)	58
1.8.2	Soils (according to DIN 18196) and construction materials suitable to a limited extent	58
1.8.3	Non-suitable soils	58
1.8.4	Natural and artificial aggregates and recycled construction materials	59
1.8.5	Sulphate influence	59
1.9	Binders	60
1.9.1	General	60

Contents

1.9.2	Types of binder	60
1.9.3	Mode of binder action	60
1.9.3.1	Building limes	60
1.9.3.2	Cements	62
1.9.3.3	Mixed binders	62
1.9.4	Binders with special properties	63
1.9.4.1	Low-dust binders	63
1.9.4.2	Hydrophobic binders	63
1.9.5	Binder applications	64
1.9.6	Binder processing times	66
1.9.7	Binder reaction times	66
1.10	Water	68
1.11	Effects of weather	70
1.11.1	Precipitation	70
1.11.2	Wind	70
1.11.3	Temperature	71
1.12	Soil treatment – Construction	72
1.12.1	Mixing procedures	72
1.12.2	Dust-free addition of binder	72
1.12.3	Mixed-in-place process	74
1.12.3.1	Principles of construction for the mixed-in-place process (all fields of soil treatment)	74
1.12.4	Requirements for soil treatment	80
1.12.4.1	Binder quantity	80
1.12.4.2	Compaction characteristics	80
1.12.4.3	Verification of binder quantity	82
1.12.4.4	Surface	82
1.12.4.5	Evenness	82
1.12.4.6	Paving thickness	82
1.13	Structural backfills	84
1.13.1	Terms	84
1.13.2	Construction materials	84
1.13.2.1	Drainage area	84
1.13.2.2	Backfill and cover fill areas	84

1.13.3	Compaction	85
1.14	Refilling utility trenches	86
1.14.1	General	86
1.14.2	Working in the binder	86
1.14.3	Compaction	86
2	Base Layers with Hydraulic Binders	91
2.1	General	91
2.2	Terminology	92
2.3	Base layers with hydraulic binders in accordance with the “Additional technical conditions of contract and directives for the construction of base layers with hydraulic binders and concrete pavements” (ZTV Beton-StB) and soil stabilization in accordance with the “Additional technical conditions of contract and directives for earthworks in road construction” (ZTV E-StB)	93
2.4	Principles of production	94
2.4.1	General	94
2.5	Tests – Definitions	95
2.5.1	Initial testing (mix design)	95
2.5.2	Factory production control	95
2.5.3	Internal control testing	97
2.5.4	Compliance testing	97
2.6	Construction materials	98
2.6.1	Soils and aggregates for soil stabilization	98
2.6.2	Aggregates and construction material mixtures for hydraulically bound base layers	99
2.6.3	Aggregates and construction material mixtures for concrete base layers	102
2.6.4	Hydraulic binders	103
2.6.5	Water	104
2.6.6	Concrete admixtures/Concrete additives	104
2.7	Requirements on base layers with hydraulic binders	105
2.7.1	Design	105
2.7.2	Pavement layers with binders	105

Contents

2.7.3	Minimum paving thicknesses	105
2.7.3.1	Stabilized layers	105
2.7.3.2	Hydraulically bound base layers	105
2.7.3.3	Concrete base layers	106
2.7.4	Edge design of base layers	106
2.7.4.1	Details of edge design	107
2.7.5	Drainage of base layers	108
2.7.6	Execution at low/high temperatures and frost	108
2.7.7	Correct vertical and horizontal position	108
2.7.8	Evenness	108
2.7.9	Tolerances of paving thickness	109
2.7.10	Grooves or joints	109
2.7.11	Curing	110
2.7.11.1	Table: Summary of requirements on base layers with hydraulic binders in accordance with the “Additional technical conditions of contract and directives for the construction of base layers with hydraulic binders and concrete pavements” (ZTV Beton-StB)	112
2.8	Producing stabilized layers	114
2.8.1	Requirements on paving mixes for stabilized layers	114
2.8.2	Production	114
2.8.3	Mixed-in-place process	114
2.8.4	Mixed-in-plant process	115
2.8.5	Placing and compaction	116
2.8.6	Requirements on the degree of compaction	116
2.9	Producing hydraulically bound base layers	117
2.9.1	Requirements on the paving mix	117
2.9.2	Production, transport and placing	117
2.9.3	Requirements on the finished layer	118
2.10	Type and scope of testing	119
2.10.1	Initial testing for stabilized layers	119
2.10.2	Initial testing for hydraulically bound base layers	121
2.10.3	Internal control and compliance testing for stabilized layers	122

2.10.4	Internal control and compliance testing for hydraulically bound base layers	124
2.10.5	Internal control and compliance testing for concrete base layers	125
2.11	Using reclaimed asphalt and reclaimed tar-bound road construction materials in base layers with hydraulic binders	126
2.11.1	General	126
2.11.2	Source materials – Aggregates	126
2.11.3	Additives	126
2.11.4	Storing reclaimed tar-bound road construction materials	127
2.11.5	Construction material mixtures	127
2.11.6	Requirements	127
2.11.7	Initial testing	127
References		128
Body of technical rules and regulations		129

1.6 Basic principles of earthworks

1.6.1 Compaction

At the start of compaction, the contractor has to complete a trial field to verify that the compaction requirements will be met.

The maximum bulk thickness (or maximum thickness of the improved layer respectively) must be such that the specified degree of compaction is achieved over the entire layer thickness.

Special conditions for compaction or construction apply to embankment shoulders. This may influence the bulk width of an embankment in case of soil stabilization or stabilization of the pavement.

When placing weather-sensitive construction materials, the bulk surfaces have to be built with a cross slope of no less than 6%.

1.6.2 Compaction requirements on subsoil and subgrade

The subsoil or subgrade of roads and paths has to be compacted so as to meet the following requirements on the minimum 10 percentile for

the degree of compaction D_{Pr} or the maximum 10 percentile for the air voids ratio n_a respectively.

Area	Soil groups	D_{Pr} in %	n_a in % by volume
Subgrade to a depth of 1.00 m for embankments Subgrade to a depth of 0.50 m for cuts	GW, GI, GE SW, SI, SE GU, GT, SU, ST	100	–
1.00 m below grade to embankment base	GW, GI, GE SW, SI, SE GU, GT, SU, ST	98	–
Subgrade to embankment base Subgrade to a depth of 0.50 m for cuts	GU*, GT*, SU*, ST* U, T, OU ¹⁾ , OT ¹⁾	97	12 ²⁾

1) These requirements apply to soils of groups OU and OT only if their suitability and placing conditions have been investigated separately and determined in consultation with the client.

2) If the soils are not improved by means of soil stabilization or qualified soil improvement, a requirement on the maximum 10 percentile for the air voids ratio is recommended as follows:
 · 8% by volume when placing water-sensitive mixed-grained or fine-grained soils; and
 · 6% by volume when placing rock of variable strength.
 This has to be indicated in the specification of works.

1.6.3 Requirements on the subgrade

The subgrade must comply with specifications in terms of correct vertical and horizontal position, evenness and bearing capacity.

Requirements on the correct vertical and horizontal position:

Deviation: ± 3 cm from design level
 ± 2 cm if the subgrade is to be overlaid with a bound base layer


The subgrade must have the following cross slope:

- > $\geq 4.0\%$ for water-sensitive soils and construction materials
- > $\geq 2.5\%$ after soil treatment with binders

Reducing the cross slope after soil treatment results in huge potential savings in pavement material.

Example: $q_{\text{Pavement}} = 2.5\%$
 $q_{\text{Subgrade}} = 4.0\%$
Width of subgrade = 6.00 m
→ **Savings: approx. 0.30 m³/m**

At the raised edge of the carriageway, the subgrade has to be designed with a reverse gradient.



When performing soil improvement operations at subgrade level, the edge design of embankment structures may require excess profiling due to the production methods and equipment used.

1.12 Soil treatment – Construction

1.12.1 Mixing procedures

A general distinction is made between two different procedures which can be used to produce a soil-binder mixture.

> **Mixed-in-plant process**

Where the mixed-in-place process cannot be used for technical reasons (due to, for example, existing manholes, gullies, road widenings, structures, trenches etc.) or is uneconomical, soil-binder mixtures produced using the mixed-in-plant process can be placed instead.

In soil treatment operations, it is usually not economically feasible to produce soil-binder mixtures using the mixed-in-plant process.

> **Mixed-in-place process**

The mixed-in-place process is the standard construction method used in soil treatment operations.

The mixer travels on the layer prepared for treatment, working in the previously spread binder and, where appropriate, the required quantity of water.

Variations in the sequence of the individual operational steps are possible depending on the location of the excavation and paving sites.

> **Special process**

Where the paving site does not allow for a mixer to be used (in case of road widenings, refilling of utility trenches or structural backfills, or in areas or locations where binder drifts must be avoided etc.), the binder can be spread and mixed in at the excavation site. The soil-binder mixture is then transported to the paving site, placed and compacted.

1.12.2 Dust-free addition of binder

The “S-Pack” (Spreader-Pack), which can be integrated into the WR 240, WR 240i or WR 250 as an optional feature, is the ideal candidate for the dustless addition of binding agents in cold recycling or soil stabilization. Lime or cement is spread right in front of the milling and mixing rotor in a microprocessor-controlled operation. “S-Pack” is synonymous with the reliable and dustless processing of binders especially on motorways, in industrial estates specifying strict emission requirements, residential areas or nature reserves.

The “S-Pack” spreader is loaded to capacity in less than five minutes. A standard 27-tonne silo transporter is emptied within two hours. The spreading process is controlled and monitored intuitively via the integrated control screen. Paired with the outstanding all-terrain mobility of the WR model range, the “S-Pack” allows binders to be spread reliably and precisely even in those places which are not suitable for the use of heavily loaded, self-propelled binder spreaders.



2.2 Terminology

Depending on the technology, source material and mixing process used, base layers with hydraulic binders are distinguished into:

> **Stabilized layers with hydraulic binders**

Soil stabilization comprises a range of construction processes aiming at increasing the resistance of granular base layers to stresses caused by traffic loading and climate.

The construction material mixture is compacted after completion of the stabilizing operation. In the process, hydraulic binders and water are added to the soils and/or construction material mixtures using the mixed-in-place or mixed-in-plant process.

- Mixed-in-place process

The mixer travels on the layer prepared for soil stabilization, scarifying it and mixing in the specified hydraulic binder and required quantity of water.

- Mixed-in-plant process

The soil or aggregate mixture is mixed with the specified binder and required quantity of water (mixing water) in stationary mixing plants, transported to the construction site and placed.

> **Hydraulically bound base layers**

(produced using the mixed-in-plant process only)

Hydraulically bound base layers consist of uncrushed and / or crushed construction material mixtures and hydraulic binders.


Grading of the construction material mixture must be within specified grading ranges. The paving mix must be produced in mixing plants.

> **Concrete base layers**

Concrete base layers are base layers of concrete in accordance with DIN EN 206-1 and DIN 1045-2.



2.3 Base layers with hydraulic binders in accordance with ZTV Beton-StB¹⁾ and soil stabilization in accordance with ZTV E-StB²⁾



¹⁾ Additional technical conditions of contract and directives for the construction of base layers with hydraulic binders and concrete pavements

²⁾ Additional technical conditions of contract and directives for earthworks in road construction

2.6.3 Aggregates and construction material mixtures for concrete base layers

Aggregates as described in section 2.6.2, Aggregates and construction material mixtures for hydraulically bound base layers, the only restriction being that suitable coal fly ash cannot be used

as an addition to the aggregates but as an additive only. The grading curves to be complied with are based on the requirements of DIN EN 206-1 and DIN 1045-2.



2.6.4 Hydraulic binders

Cements in accordance with DIN EN 197 or DIN 1164-10 as shown in the table below or hydraulic soil and road binders in accordance

with DIN 18506 (strength classes 12.5 and 32.5) are used as binders.

Main types of cement	Designation of cement types	Main constituents	
CEM I	Portland cement		
CEM II	Portland blast-furnace slag cement	A/B	S Granulated blast-furnace slag
	Portland silica fume cement	A	D Silica fume
	Portland pozzolanic cement	A/B	P/Q Pozzolans
	Portland fly ash cement	A	V Fly ash
	Portland burnt shale cement	A/B	T Shale
	Portland limestone cement	A	LL Limestone
CEM II-M	Portland composite cement	A	S-D, S-T, S-LL
			S-P, S-V
			D-T, D-LL, D-P
			D-V
			T-LL
			P-V, P-T, P-LL
			V-T, V-LL
		B	S-D, S-T, S-P
			D-T, D-P
			P-T
CEM III	Blast-furnace slag cement	A	S
		B	S
CEM IV	Pozzolanic cement	B	P ¹⁾
CEM V	Composite cement	A	S-P ²⁾
		B	

¹⁾ Applies only to trass according to DIN 51043 as the main constituent of up to max. 40% by mass

²⁾ Applies only to trass according to DIN 51043 as the main constituent